MOORING ROPE

SPM Rope

ISO9001 Supplier

Class Certificate

Export Supply

Material:polyamide(nylon 66). Construction:Load-bearing cores with a protective cover of polyamide. Application:offshore. Colour of rope:white with green marker. Specific gravity:Density 1.14 non ...



Key Highlights

Category	Mooring Rope
Standard	EN
Material	Material:polyamide(nylon 66).
Weight / Size	Weight:±5%tolerance.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Mooring Rope	**Model / SKU**	SPM-Rope
Standard	EN	**Material**	Material:polyamide(nylon 66).
Weight / Size	Weight:±5%tolerance.	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

China SPM Rope:

Material:polyamide(nylon 66).

Construction:Load-bearing cores with a protective cover of polyamide.

Application:offshore.

Colour of rope:white with green marker.

Specific gravity:Density 1.14 non floating.

Melting point:215 centigrade.

Abrasion resistance:excellent. U.V resistance: Excellent.

Temperature resistance: 80 centigrade max continuous.

Chemical resistance: reasonable,acids,oxidizer and solvents will affect nylon.

Dry& wet conditions: wet strength ±5% than dry strength

SPM polyamide hawsers are manufactured in accordance with OCIMF 2000 regulations. Weight:±5%tolerance.

