

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

ELECTRIC HEATER

## SS-250 Marine Meat Slicer

SS-250&nbsp;Marine&nbsp;Meat&nbsp;Slicer Product introduction: 1. Aluminium magnesium alloy casting, polishing surface anodic oxidation treatment; 2. The Aluminum Alloy handle, metal button switch; ...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

|               |  |
|---------------|--|
| Category      | Electric Heater  |
| Standard      | EN   |
| Material      | SS304  |
| Weight / Size | Model Dimension(mm) Blade Daimeter Power (kw) Volts(v) HZ N/W(kg) SS-25... |
| Certificate   | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS                                 |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

|               |  |             |  |
|---------------|--|-------------|--|
| Category      | Electric Heater  | Model / SKU | SS-250-Marine-Meat-Slicer  |
| Standard      | EN   | Material    | SS304  |
| Weight / Size | Model Dimension(mm) Blade Daimeter Power (kw) Volts(v) HZ N/W(kg) SS-250 550x450x390 φ250mm 0.15 220V-1P 50/60Hz 18 SS-300 680x510x440 φ300mm 0.3 220V-1P 50/60Hz 21 | Surface     | Aluminium magnesium alloy casting, polishing surface anodic oxidation treatment; |
| Certificate   | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS   | Warranty    | 12 Months unless specified otherwise   |
| Origin        | China  |             |  |

CONTENTS

■ Product introduction:

■ Technical data:

## Product introduction:

1. Aluminium magnesium alloy casting, polishing surface anodic oxidation treatment;
2. The Aluminum Alloy handle, metal button switch;
3. The Guard cutter disassembly safety protection, safety protection to cut meat and;
4. The stainless steel blades, gear transmission;
5. The suction type fixed.

## Technical data:

| Model  | Dimension(mm) | Blade Daimeter | Power (kw) | Volts(v) | HZ      | N/W(kg) |
|--------|---------------|----------------|------------|----------|---------|---------|
| SS-250 | 550x450x390   | φ250mm         | 0.15       | 220V-1P  | 50/60Hz | 18      |
| SS-300 | 680x510x440   | φ300mm         | 0.3        | 220V-1P  | 50/60Hz | 21      |