SEWAGE TREATMENT PLANT

SWCM-50 Sewage Treatment Plant

ISO9001 Supplier

Class Certificate

Export Supply

Product Description: The SWCM type marine sewage treatment plant uses activated sludge, contact oxidizing and principle of biologic membrane to digest the organic pollutant, which can treat sewage effectively a...



Key Highlights

Category	Sewage Treatment Plant
Standard	GB
Weight / Size	Model LOAD Rated capacity （men） Max capacity （men） External dimension （mm） L...
Certificate	CCS GL BV

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Sewage Treatment Plant	**Model / SKU**	SWCM-50-Sewage-Treatment-Plant
Standard	GB	**Weight / Size**	Model LOAD Rated capacity （men） Max capacity（men） External dimension（mm）L×W×H weight Average load（L/d） Peak load（L/h） Organic load(kgBOD5/d） Dry weight （kg） Wet weight（kg） SWCM-10 840 105 0.42 10 12 1510×1200x1300 900 1775 SWCM-15 1190 149 0.595 15 17 1870x1200x1400 1000 2283 SWCM-20 1540 193 0.77 20 22 1745x1400x1525 1000 2640 SWCM-25 1890 237 0.945 25 27 1935x1400x1560 1100 2740 SWCM-30 2310 289 1.155 30 33 1985x1500x1650 1200 3500 SWCM-40 3080 385 1.54 40 44 2400x1600x1700 1300 4400 SWCM-50 3780 473 1.89 50 54 2410x1700x1850 1450 5073 SWCM-60 4480 560 2.24 60 64 2670x1700x1850 1600 5270 SWCM-80 6020 753 3.01 80 86 2780x1900x2050 1850 6517 SWCM-100 7700 963 3.85 100 110 2795x2000x2200 2200 8268 SWCM-120 9100 1138 4.55 120 130 3000x2000x2200 2300 9166 SWCM-150 11200 1400 5.
Certificate	CCS GL BV	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS


- Product Description:
- Technical Data:
- Working Principle:

Product Description:

The SWCM type marine sewage treatment plant uses activated sludge, contact oxidizing and principle of biologic membrane to digest the organic pollutant, which can treat sewage effectively and reach at the IMO new effluent standard or other stricter requirements.

Working Principle:

The device adopts activated sludge, contact oxidizing and principle of biologic membrane to digest the organic pollutant, which can treat sewage effectively andmeetthe IMO new effluent standard or other stricter requirements.



Technical Data:

Model	LOAD			Rated capacity (men)	Max capacity (men)	External dimension (mm) L×W×H	weight	
	Average load (L/d)	Peak load (L/h)	Organic load(kgBOD5/ d)				Dry weight (kg)	Wet weight (kg)
SWC M-10	840	105	0.42	10	12	1510×1200x1300	900	1775
SWC M-15	1190	149	0.595	15	17	1870x1200x1400	1000	2283
SWC M-20	1540	193	0.77	20	22	1745x1400x1525	1000	2640
SWC M-25	1890	237	0.945	25	27	1935x1400x1560	1100	2740
SWC M-30	2310	289	1.155	30	33	1985x1500x1650	1200	3500
SWC M-40	3080	385	1.54	40	44	2400x1600x1700	1300	4400
SWC M-50	3780	473	1.89	50	54	2410x1700x1850	1450	5073
SWC M-60	4480	560	2.24	60	64	2670x1700x1850	1600	5270
SWC M-80	6020	753	3.01	80	86	2780x1900x2050	1850	6517
SWC M-100	7700	963	3.85	100	110	2795x2000x2200	2200	8268
SWC M-120	9100	1138	4.55	120	130	3000x2000x2200	2300	9166
SWC M-150	11200	1400	5. 6	150	160	3050x2200x2300	2800	11340
SWC M-200	14700	1838	7.35	200	210	3600x2200x2350	3000	13267
SWC M-250	18200	2275	9.1	250	260	3880x2400x2570	3300	16538

SWC M-300	23100	2888	11.55	300	330	4750x2400x2570	3700	20357
SWC M-400	30800	3850	15.4	400	440	5950x2400x2570	4200	25417