

## FILTER

## SZL20 Model Double-Cylinder Paper Filter

ISO9001 Supplier

Class Certificate

Export Supply

SZL20 Model Double-Cylinder Paper Filter The filter model representation is as follows:

SZL → SBL represent the double berrelled 65 → 200 representations passes diameters 200mm

Work pressure ...

Loading product image...

### Key Highlights

<b>Category</b>	Filter
<b>Standard</b>	ISO
<b>Weight / Size</b>	Model Current capacity(referencem <sup>3</sup> /h) Passes the diameter and the joint ...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Filter	Model / SKU	SZL20-Model-Double-Cylinder-Paper-Filter
Standard	ISO	Weight / Size	Model Current capacity(referencem <sup>3</sup> /h) Passes the diameter and the joint size(mm) External dimensions(mm) Installing size(mm) Weight(kg) DN K E R r 4-M1 H1 H2 L $\phi$ N P W V Y Z 4-M2 SZL20 0.5-1.5 20 60 50 22 12 10 320 60 95 85 193 184 100 53 75 35 10 8 SZL25 1.5-2 25 62 55 25 12 10 375 77 110 98 216 206 100 70 80 40 10 3 SZL25 2-4 32 75 70 35 15 12 420 90 130 125 264 226 120 80 90 40 12 19 SZL25 4-6 40 75 70 35 15 12 445 90 130 125 264 226 120 80 90 40 12 22 DN D D1 E N-M1 H1 L N P Y Z N-D SZL65A I 25-50 65 184 145 190 8-M16 597 220 510 268 474 320 4- $\phi$ 14 SZL65A II 40-80 65 184 145 190 8-M16 780 220 510 268 474 320 4- $\phi$ 14
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

**CONTENTS**

- SZL20 Model Double-Cylinder Paper Filter

- SZL20 Model Double-Cylinder Paper Filter Technical Parameters:

## SZL20 Model Double-Cylinder Paper Filter

The filter model representation is as follows:

SZL → SBL represent the double berrelled

65 → 200 representations passes diameters 200mm

Work pressure	Flow	Safe filter cylinder precision	Normal using precision	Pressure difference of safe value opening	Pressure difference of by-pass valve opening
0.06Mpa	2x25m <sup>3</sup> /h	60um	10-15um	0.2±0.02Mpa	0.4±0.02Mpa



## SZL20 Model Double-Cylinder Paper Filter Technical Parameters:

Model	Current capacity( reference m³/h)		Passes the diameter and the joint size(mm)					External dimensions(mm)							Installing size(mm)				Weight(kg)	
			D N	K	E	R	r	4-M1	H1	H 2	L	φ	N	P	W	V	Y	Z		4-M2
SZL20	0.5-1.5		20	60	50	22	1 2	10	32 0	60	95	85	19 3	18 4	10 0	5 3	7 5	3 5	10	8
SZL25	1.5-2		25	62	55	25	1 2	10	37 5	77	11 0	98	21 6	20 6	10 0	7 0	8 0	4 0	10	3
SZL25	2-4		32	75	70	35	1 5	12	42 0	90	13 0	12 5	26 4	22 6	12 0	8 0	9 0	4 0	12	19
SZL25	4-6		40	75	70	35	1 5	12	44 5	90	13 0	12 5	26 4	22 6	12 0	8 0	9 0	4 0	12	22
DN	D	D1	E	N-M1		H1		L	N		P		Y	Z	N-D					
SZL65A I	25-50		65	18 4	14 5	19 0	8-M16		597		22 0	510		268		4 7 4	3 2 0	4-φ14		
SZL65A II	40-80		65	18 4	14 5	19 0	8-M16		780		22 0	510		268		4 7 4	3 2 0	4-φ14		