

## FILTER

## SZL25 Model Double-Cylinder Paper Filter

ISO9001 Supplier

Class Certificate

Export Supply

SZL25 Model Double-Cylinder Paper Filter The filter model representation is as follows:

SZL → SBL represent the double berrelled 65 → 200 representations passes diameters 200mm

Work pressure ...

Loading product image...

### Key Highlights

<b>Category</b>	Filter
<b>Standard</b>	ISO
<b>Weight / Size</b>	SZL → SBL represent the double berrelled 65 → 200 representations passes dia...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	Filter	<b>Model / SKU</b>	SZL25-Model-Double-Cylinder-Paper-Filter
<b>Standard</b>	ISO	<b>Weight / Size</b>	<p>SZL → SBL represent the double berrelled 65 → 200 representations passes diameters 200mm Work pressure Flow Safe filter cylinder precision Normal using precision Pressure difference of safe value opening Pressure difference of by-pass valve opening 0.06Mpa 2x25m³/h 60um 10-15um 0.2±0.02Mpa 0.4±0.02Mpa SZL25 Model Double-Cylinder Paper Filter Technical Parameters:</p> <p>Model Current capacity(referencem³/h) Passes the diameter and the joint size(mm) External dimensions(mm) Installing size(mm) Weight(kg) DN K E R r 4-M1 H1 H2 L φ N P W V Y Z 4-M2 SZL20 0.5-1.5 20 60 50 22 12 10 320 60 95 85 193 184 100 53 75 35 10 8 SZL25 1.5-2 25 62 55 25 12 10 375 77 110 98 216 206 100 70 80 40 10 3 SZL25 2-4 32 75 70 35 15 12 420 90 130 125 264 226 120 80 90 40 12 19 SZL25 4-6 40 75 70 35 15 12 445 90 130 125 264 226 120 80 90 40 12 22 DN D D1 E N-M1 H1 L N P Y Z N-D SZL65A I 25-50 65 184 145 190 8-M16 597 220 510 268 474 320 4-φ14 SZL65A II 40-80 65 184 145 190 8-M16 780 220 510 268 474 320 4-φ14</p>
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

**CONTENTS**

- SZL25 Model Double-Cylinder Paper Filter

- SZL25 Model Double-Cylinder Paper Filter Technical Parameters:



## SZL25 Model Double-Cylinder Paper Filter

The filter model representation is as follows:

SZL → SBL represent the double berrelled

65 → 200 representations passes diameters 200mm

Work pressure	Flow	Safe filter cylinder precision	Normal using precision	Pressure difference of safe value opening	Pressure difference of by-pass valve opening
0.06Mpa	2x25m <sup>3</sup> /h	60um	10-15um	0.2±0.02Mpa	0.4±0.02Mpa

## SZL25 Model Double-Cylinder Paper Filter Technical Parameters:

Model	Current capacity( reference m <sup>3</sup> /h)		Passes the diameter and the joint size(mm)					External dimensions(mm)							Installing size(mm)				Weight(kg)	
			D N	K	E	R	r	4-M1	H1	H 2	L	φ	N	P	W	V	Y	Z		4-M2
SZL20	0.5-1.5		20	60	50	22	12	10	320	60	95	85	193	184	100	53	75	35	10	8
SZL25	1.5-2		25	62	55	25	12	10	375	77	110	98	216	206	100	70	80	40	10	3
SZL25	2-4		32	75	70	35	15	12	420	90	130	125	264	226	120	80	90	40	12	19
SZL25	4-6		40	75	70	35	15	12	445	90	130	125	264	226	120	80	90	40	12	22
DN	D	D1	E	N-M1		H1		L	N		P	Y	Z	N-D						
SZL65A I	25-50		65	184	145	190	8-M16		597	220	510		268		44	37	4-φ14			
SZL65A II	40-80		65	184	145	190	8-M16		780	220	510		268		44	37	4-φ14			