

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MARINE BATTERYLESS TELEPHONE SYSTEM

Safety Barrier

Safety Barrier

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category Marine Batteryless Telephone System

Standard EN

Material 2-PG16 Hull Material:

Weight / Size

Certificate ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Batteryless Telephone System	Model / SKU	Safety-Barrier
Standard	EN	Material	2-PG16 Hull Material:
Weight / Size	<=118mA Leakage Current:	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

 0.041761s

China Safety Barrier:



Type: AQ-1
Color: Pantone642c
Explosion-proof Grade: ExibIIc
Cable Gland: 2-PG16
Hull Material: Aluminum
Max. Power Supply: $\leq 17V$
Ma. Output Current: $\leq 118mA$
Leakge Current: $\leq 10 \mu A$
Installation: Wall Mount Type

To be installed in safety area, connection to exproof batteryless telephone.