

STEEL PIPE

# Schedule 80 Carbon Steel Pipe

Product Description: Our seamless steel pipes are in accordance with a wide range of standards, like ASME B16.9, ISO, API, EN, DIN BS, JIS, and GB, etc. Size: 1/2" - 24" seamless steel pipe Outer Diameter:...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

Category	Steel Pipe
Standard	JIS
Material	Carbon steel, A53B, A106B, API 5L B, X42, X46, X52, X60, X65, ect
Weight / Size	Size: 1/2" - 24" seamless steel pipe Outer Diameter: 21.3 - 609.6 mm Thick...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

Category	Steel Pipe	Model / SKU	Schedule-80-Carbon-Steel-Pipe
Standard	JIS	Material	Carbon steel, A53B, A106B, API 5L B, X42, X46, X52, X60, X65, ect
Weight / Size	Size: 1/2" - 24" seamless steel pipe Outer Diameter: 21.3 - 609.6 mm Thickness: 3.73 - 30.96 mm, Schedule 80 Material: Carbon steel, A53B, A106B, API 5L B, X42, X46, X52, X60, X65, ect Technique: Cold Drawn, Hot Rolled, Hot Expand ect Specification:	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China



## CONTENTS

■ Product Description:

■ Specification:

## Product Description:

Our seamless steel pipes are in accordance with a wide range of standards, like ASME B16.9, ISO, API, EN, DIN, BS, JIS, and GB, etc.

Size: 1/2" - 24" seamless steel pipe

Outer Diameter: 21.3 - 609.6 mm

Thickness: 3.73 - 30.96 mm, Schedule 80

Material: Carbon steel, A53B, A106B, API 5L B, X42, X46, X52, X60, X65, etc

Technique: Cold Drawn, Hot Rolled, Hot Expand etc

## Specification:

Nominal diameter		Outer diameter mm	Wall thickness and theoretical weight	
DN	in		SCH80	
			mm	m/kg
10	1/8	17	3.5	1.17
15	1/2	21.3	3.6	1.57
20	3/4	26.9	4.0	2.26
25	1	33.7	4.5	3.24
32	1 1/4	42.4	5.0	4.61
40	1 1/2	48.3	5.0	5.34
50	2	60.3	5.6	7.55
65	2 1/2	76.1	7.1	12.08
80	3	88.9	8.0	15.96
100	4	114.3	8.8	22.89
125	5	139.7	10.0	31.98
150	6	168.3	11.0	42.67
200	8	219.1	12.5	63.68
250	10	273	16.0	101.40
300	12	323.9	17.5	132.23
350	14	355.6	20.0	165.52
400	16	406.4	22.2	210.33
450	18	457	24.0	256.27
500	20	508	26.0	309.04



0.048440s

550	22	559	28.0	366.64
600	24	610	32.0	456.11

