MARINE PAINT

Self-Polishing-Antifouling-Paint

ISO9001 Supplier

Class Certificate

Export Supply

Characteristics 1. Long-term antifouling coatings. Effectively protect ship bottom against marine growths such as barnacle, oyster, bryozoans and algae. 2. Keep film surface smooth under the action ...



Key Highlights

Category	Marine Paint
Standard	DIN
Weight / Size	Color Iron red Solid Content 75% Specific Gravity 1.8 Coverage Rate Theo...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Paint	**Model / SKU**	Self-Polishing-Antifouling-Paint
Standard	DIN	**Weight / Size**	Color Iron red Solid Content 75% Specific Gravity 1.8 Coverage Rate Theoretical:0.28kg/m2/100μm 0.172L/m2/100μm Actual:
Surface	Keep film surface smooth under the action of hydrolysis.	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- Characteristics
- Basic Information

Characteristics

1. Long-term antifouling coatings. Effectively protect ship bottom against marine growths such as barnacle, oyster, bryozoans and algae.

2. Keep film surface smooth under the action of hydrolysis.

3. One coat can reaches 100μm of the film thickness; good workability.

Basic Information

Uses	As antifouling paint for the hull under boot tops.
Color	Iron red
Solid Content	75%
Specific Gravity	1.8
Coverage Rate	Theoretical:0.28kg/m2/100μm 0.172L/m2/100μm Actual: depending on the surface treatment, environment and application methods.
Thinner	Thinner for self-polishing paint
Mixing Ratio	One-pack
Film Thickness	Dry film thickness:100μm /coat Wet film thickness:200μm/coat
Coating System	Substrate: coated with vinyl tie coat Preceding Coat :refer to our coating system.
Surface Preparation	Remove oil and grease with a suitable detergent or degreaser. Remove dust and dirt by high-pressure air before paint application. Confirm the surface clean and dry.