

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

LIFE RAFT

Self-Righting Inflatable Liferafts

Appliance Scope: Lifesaving for the ship's passengers in international voyage. Available

Model: Type KHZ-6 KHZ-10 KHZ-15 ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Life Raft
Standard	EN
Weight / Size	Type KHZ-6 KHZ-10 KHZ-15 KHZ-20 KHZ-25 KHZ-50 KHZ- 100 KHZ-110 KHZ-125 Ph...
Certificate	CCS,EC

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	Life Raft	Model / SKU	Self-Righting-Inflatable-Liferafts
Standard	EN	Weight / Size	Type KHZ-6 KHZ-10 KHZ-15 KHZ-20 KHZ-25 KHZ-50 KHZ-100 KHZ-110 KHZ-125 Physical form rectangular octagon rectangular octagon rectangular octagon rectangular octagon rectangular dodecagon rectangular dodecagon rectangular dodecagon Capacity 6 10 15 20 25 50 100 110 125 Length (mm) , ±1000 2800 3510 4300 4900 5300 7311 11060 11550 12000 Width (mm) , ±1000 1660 2000 2400 2700 3100 4240 5260 5600 6100 Height (mm) , ±50 1500 1700 2050 2250 2350 3000 3250 3450 3650 Pack Dia (mm) 615 670 690 730 745 895 1050 1050 1050 Length (mm) 1095 1135 1285 1440 1485 2095 2400 2400 2400 Weight , kg ≤ 85 114 142 185 212 445 780 860 920
Certificate	CCS,EC	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ Appliance Scope:	■ Available Model:
-----------------	--------------------	--------------------

Appliance Scope:

Lifesaving for the ship's passengers in international voyage.

Available Model:

Type	KHZ-6	KHZ-10	KHZ-15	KHZ-20	KHZ-25	KHZ-50	KHZ-100	KHZ-110	KHZ-125
Physical form	rectangular octagon	rectangular octagon	rectangular octagon	rectangular octagon	rectangular octagon	rectangular dodecagon	rectangular dodecagon	rectangular dodecagon	rectangular dodecagon
Capacity	6	10	15	20	25	50	100	110	125
Length (mm) , ±1000	2800	3510	4300	4900	5300	7311	11060	11550	12000



Width (mm) , ±1000		1660	2000	2400	2700	3100	4240	5260	5600	6100
Height (mm) , ±50		1500	1700	2050	2250	2350	3000	3250	3450	3650
Pack	Dia (mm)	615	670	690	730	745	895	1050	1050	1050
	Length (mm)	1095	1135	1285	1440	1485	2095	2400	2400	2400
Weight , kg ≤		85	114	142	185	212	445	780	860	920