

ELECTRIC OPERATED FIRE MONITOR

Self Suction Type Electrical Foam And Water Fire Monitor 64L/S

- ISO9001 Supplier
- Class Certificate
- Export Supply

Type: JBPLKD64 Flow Range: 64L/S (1000GPM) Working Pressure: 10 bar~ 12 bar Max Reach @ Max Flow: 80m (water) and 75M (foam) Max. Range of motion: +/-90°Vert , 350°Rot Turning speed : 18 degrees/sec Material (body) : 304L...



Key Highlights

Category	Electric Operated Fire Monitor
Standard	EN
Material	+/-90°Vert , 350°Rot Turning speed : 18 degrees/sec Material (body) : 304L S...
Weight / Size	+/-90°Vert , 350°Rot Turning speed : 18 degrees/sec Material (body) : 304L S...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	Electric Operated Fire Monitor	Model / SKU	Self-Suction-Type-Electrical-Foam-And-Water-Fire-Monitor-64L-S
Standard	EN	Material	+/-90°Vert , 350°Rot Turning speed : 18 degrees/sec Material (body) : 304L Stainless Steel, 316L Stainless Steel is also available Material (Gear) : bronze Material (nozzle) : Aluminum power supply : 12/24VDC or 100-230VAC Power Consumption normal/Max : 50W/150W Weight incl.
Weight / Size	+/-90°Vert , 350°Rot Turning speed : 18 degrees/sec Material (body) : 304L Stainless Steel, 316L Stainless Steel is also available Material (Gear) : bronze Material (nozzle) : Aluminum power supply : 12/24VDC or 100-230VAC Power Consumption normal/Max : 50W/150W Weight incl.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China Self Suction Type Electrical Foam And Water Fire Monitor 64L/S:

Type: JBPLKD64

Flow Range: 64L/S (1000GPM)

Working Pressure: 10 bar~ 12 bar

Max Reach @ Max Flow: 80m (water) and 75M (foam)

Max. Range of motion: +/-90°Vert , 350°Rot

Turning speed : 18 degrees/sec

Material (body) : 304L Stainless Steel, 316L Stainless Steel is also available

Material (Gear) : bronze

Material (nozzle) : Aluminum

power supply : 12/24VDC or 100-230VAC

Power Consumption normal/Max : 50W/150W

Weight incl. nozzle : appox 26kg

Cable Length Monitor- CPU : 5m

Cable Length Joystick-CPU : 5m standard/ other length available

Pump requirement for minimum performance : 64L/S@ 10 bar

Pipe dimensions for installation: 3 Inch

Monitor Inlet : 3" male BSP or DN100 flange

Monitor Outlet : 2.5 inch (65mm)

Water way size: 3 inch

PACKAGE: SS MONITOR, NOZZLE, CONTROL BOX, JOYSTICK, CABLES, WIRELESS CONTROL  0.080186s