HIGH PRESSURE PUMP

Single Acting Hollow Jack

Single Acting Hollow Jack   Product features: Single-acting design, spring return,easy to use. Hollow plunger design can be used for both pull and push. Painted surface for greater corrosion resistance. Equipp...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	High Pressure Pump
Standard	EN
Weight / Size	Model TCapacity mm Stroke mm Height mmMax Heigh mmDiameter mmDiame...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	High Pressure Pump	**Model / SKU**	Single-Acting-Hollow-Jack
Standard	EN	**Weight / Size**	Model TCapacity mm Stroke mm Height mmMax Heigh mmDiameter mmDiameter kgWeight RCH-120 12 8 56 63 70 19.6 1.5 RCH-121 12 41 121 162 70 19.6 2.8 RCS-1211 12 41 121 162 70 19.6 2.8 RCH-123 12 76 184 260 70 19 4.4 RCH-202 20 51 162 213 99 26.9 7.7 RCH-206 20 155 306 461 99 26.9 14.1 RCH - 302 30 63 179 242 114 33.3 10.9 RCH-306 30 156 330 486 114 33.3 21.8 RCH-603 60 76 248 324 159 53.8 28.1 RCH-606 60 152 324 476 159 53.8 35.4 RCH-1003 100 76 254 330 213 79 59.9
Surface	Painted	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

China Single Acting Hollow Jack:

Single Acting Hollow Jack

Product features:

Single-acting design, spring return,easy to use.

Hollow plunger design can be used for both pull and push.

Painted surface for greater corrosion resistance.

Equipped with a dust ring to reduce pollution and extend the life of the hydraulic cylinder.

All models include quick connectors and dust protection.

Model	T Capacity	mm Stroke	mm Height	mm Max Heigh	mm Diameter	mm Diameter	kg Weight
RCH-120	12	8	56	63	70	19.6	1.5
RCH-121	12	41	121	162	70	19.6	2.8
RCS-1211	12	41	121	162	70	19.6	2.8
RCH-123	12	76	184	260	70	19	4.4
RCH-202	20	51	162	213	99	26.9	7.7
RCH-206	20	155	306	461	99	26.9	14.1

RCH - 302	30	63	179	242	114	33.3	10.9
RCH-306	30	156	330	486	114	33.3	21.8
RCH-603	60	76	248	324	159	53.8	28.1
RCH-606	60	152	324	476	159	53.8	35.4
RCH-1003	100	76	254	330	213	79	59.9