HIGH PRESSURE PUMP

Single Acting Jack

Single Acting Jack   Product features: Can be used anywhere. Single-acting design, spring return,easy to use. High-strength alloys are durable. Equipped with a dust ring to reduce pollution and extend the life...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	High Pressure Pump
Standard	EN
Weight / Size	Model TCapacity mm Stroke mm Height mmMax Heigh mmDiameter mmrod...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	High Pressure Pump	**Model / SKU**	Single-Acting-Jack
Standard	EN	**Weight / Size**	Model TCapacity mm Stroke mm Height mmMax Heigh mmDiameter mmrod diameter mmDiameter kgWeight RC-50 5 16 41 57 40 36 55 1 RC-51 25 90 115 55 1 RC-53 76 145 221 55 1.5 RC-55 127 196 323 55 1.9 RC-57 178 253 431 55 2.4 RC-59 232 304 536 55 2.8 RC-101 10 25 80 105 45 41 60 1.8 RC-102 54 111 165 60 2.3 RC-104 105 161 266 60 3.3 RC-106 156 238 394 60 4.4 RC-108 203 288 491 60 5.4 RC-1010 257 339 596 60 6.4 RC-1012 305 390 695 60 6.8 RC-1014 356 441 797 60 8.2 RC-151 15 25 104 129 55 46 70 3.3 RC-152 51 129 180 70 4.1 RC-154 102 180 282 70 5 RC-156 152 252 404 70 6.8 RC-158 203 302 505 70 8.2 RC-1510 254 353 607 70 9.5 RC-1512 305 404 709 70 10.9 RC-1514 356 455 811 70 11.8 RC-251 25 25 120 145 70 62 90 5.9 RC-252 51 145 196 90 6.4 RC-254 102 196 298 90 8.2 RC-256 159 253 412 90 10 RC-258 210 304 514 90 12.3 RC-2510 260 355 615 90 14.1 RC-2512 311 405 716 90 16.3 RC-2514 362 456 81 90 17.1 RC-308 30 210 337 547 80 65 104 18.1 RC-502 50 51 136 187 100 80 127 15 RC-504 102 187 289 127 19.1 RC-506 159 243 402 127 23.2 RC-5013 337 421 758 127 37.7 RC-756 75 156 246 402 125 90 160 29.5 RC-7513 334 452 786 160 59 RC-1006 100 168 267 435 140 100 180 59 RC-10010 260 359 619 180 72.6
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

China Single Acting Jack:

Single Acting Jack

Product features:

Can be used anywhere.

Single-acting design, spring return,easy to use.

High-strength alloys are durable.

Equipped with a dust ring to reduce pollution and extend the life of the hydraulic cylinder.

Some models have handles for easy movement.

All models include quick connectors and dust caps.

Model	T Capacity	mm Stroke	mm Height	mm Max Heigh	mm Diameter	mm rod diameter	mm Diameter	kg Weight
RC-50	5	16	41	57	40	36	55	1
RC-51		25	90	115			55	1
RC-53		76	145	221			55	1.5
RC-55		127	196	323			55	1.9
RC-57		178	253	431			55	2.4
RC-59		232	304	536			55	2.8
RC-101	10	25	80	105	45	41	60	1.8
RC-102		54	111	165			60	2.3
RC-104		105	161	266			60	3.3
RC-106		156	238	394			60	4.4
RC-108		203	288	491			60	5.4
RC-1010		257	339	596			60	6.4
RC-1012		305	390	695			60	6.8
RC-1014		356	441	797			60	8.2
RC-151	15	25	104	129	55	46	70	3.3
RC-152		51	129	180			70	4.1
RC-154		102	180	282			70	5
RC-156		152	252	404			70	6.8
RC-158		203	302	505			70	8.2
RC-1510		254	353	607			70	9.5
RC-1512		305	404	709			70	10.9
RC-1514		356	455	811			70	11.8

RC-251	25	25	120	145	70	62	90	5.9
RC-252		51	145	196			90	6.4
RC-254		102	196	298			90	8.2
RC-256		159	253	412			90	10
RC-258		210	304	514			90	12.3
RC-2510		260	355	615			90	14.1
RC-2512		311	405	716			90	16.3
RC-2514		362	456	81			90	17.1
RC-308	30	210	337	547	80	65	104	18.1
RC-502	50	51	136	187	100	80	127	15
RC-504		102	187	289			127	19.1
RC-506		159	243	402			127	23.2
RC-5013		337	421	758			127	37.7
RC-756	75	156	246	402	125	90	160	29.5
RC-7513		334	452	786			160	59
RC-1006	100	168	267	435	140	100	180	59
RC-10010		260	359	619			180	72.6