

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

HIGH PRESSURE PUMP

Single-Acting Short, Medium And Long Jacks

- ISO9001 Supplier
- Class Certificate
- Export Supply

Single-Acting Short, Medium And Long Jacks Model TCapacity
 cm²;Area LOilcapacity mmHeight mmMaxHeight mmOutsidedia mmCylinderbore
 dia mmPlungerdia mmoil inletthread mmb...



Key Highlights

| | |
|---------------|--|
| Category | High Pressure Pump |
| Weight / Size | Single-Acting Short, Medium And Long Jacks Model TCapacity cm ² Ar... |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

| Technical Specifications | | | |
|--------------------------|---|--------------------|--|
| Category | High Pressure Pump | Model / SKU | Single-Acting-Short-Medium-And-Long-Jacks |
| Weight / Size | Single-Acting Short, Medium And Long Jacks Model TCapacity cm²Area LOilcapacity mmHeight mmMaxHeight mmOutsidedia mmCylinderboredia mmPlungerdia mmoil inletthread mmbulgeheight kgWeight RSC1050 10 13.8 0.073 107 157 64 46 40 3/8'-19 17 3 RSC10100 10 13.8 0.145 155 255 64 46 40 3/8'-19 17 3.5 RSC10150 10 13.8 0.22 206 361 64 46 40 3/8'-19 17 4.3 RSC2050 20 26.4 0.14 107 157 80 60 50 3/8'-19 20 5.5 RSC20100 20 26.4 0.28 155 255 80 60 50 3/8'-19 20 3 RSC20150 20 26.4 0.42 206 361 80 60 50 3/8'-19 20 10 RSC3050 30 41.8 0.208 112 162 100 80 70 3/8'-19 20 6.8 RSC30100 30 41.8 0.416 160 260 100 80 70 3/8'-19 20 12.5 RSC30150 30 41.8 0.624 211 361 100 80 70 3/8'-19 20 14.5 RSC5050 50 78.5 0.35 112 162 130 100 80 3/8'-19 26 9.8 RSC50100 50 78.5 0.7 160 260 130 100 80 3/8'-19 26 18 RSC50150 50 78.5 1.06 211 361 130 100 80 3/8'-19 26 22 RSC10050 100 103.8 0.66 122 172 180 125 110 3/8'-19 28 24 RSC100100 100 103.8 13.2 171 271 180 125 110 3/8'-19 28 30 RSC100150 100 103.8 17.3 221 371 180 125 110 3/8'-19 28 45 | Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |
| Warranty | 12 Months unless specified otherwise | Origin | China |

China Single-Acting Short, Medium And Long Jacks:

Single-Acting Short, Medium And Long Jacks

| Model | T Capacity | cm² Area | L Oil capacity | mm Height | mm Max Height | mm Outside dia | mm Cylinder boredia | mm Plunger dia | mm oil inlet thread | mm bulge height | kg Weight |
|-------|------------|----------|----------------|-----------|---------------|----------------|---------------------|----------------|---------------------|-----------------|-----------|
| | | | | | | | | | | | |

| | | | | | | | | | | | |
|---------------|-----|-------|-------|-----|-----|-----|-----|-----|---------|----|------|
| RSC10 50 | 10 | 13.8 | 0.073 | 107 | 157 | 64 | 46 | 40 | 3/8'-19 | 17 | 3 |
| RSC10 100 | 10 | 13.8 | 0.145 | 155 | 255 | 64 | 46 | 40 | 3/8'-19 | 17 | 3.5 |
| RSC10 150 | 10 | 13.8 | 0.22 | 206 | 361 | 64 | 46 | 40 | 3/8'-19 | 17 | 4.3 |
| RSC20 50 | 20 | 26.4 | 0.14 | 107 | 157 | 80 | 60 | 50 | 3/8'-19 | 20 | 5.5 |
| RSC20 100 | 20 | 26.4 | 0.28 | 155 | 255 | 80 | 60 | 50 | 3/8'-19 | 20 | 3 |
| RSC20 150 | 20 | 26.4 | 0.42 | 206 | 361 | 80 | 60 | 50 | 3/8'-19 | 20 | 10 |
| RSC30 50 | 30 | 41.8 | 0.208 | 112 | 162 | 100 | 80 | 70 | 3/8'-19 | 20 | 6.8 |
| RSC30 100 | 30 | 41.8 | 0.416 | 160 | 260 | 100 | 80 | 70 | 3/8'-19 | 20 | 12.5 |
| RSC30 150 | 30 | 41.8 | 0.624 | 211 | 361 | 100 | 80 | 70 | 3/8'-19 | 20 | 14.5 |
| RSC50 50 | 50 | 78.5 | 0.35 | 112 | 162 | 130 | 100 | 80 | 3/8'-19 | 26 | 9.8 |
| RSC50 100 | 50 | 78.5 | 0.7 | 160 | 260 | 130 | 100 | 80 | 3/8'-19 | 26 | 18 |
| RSC50 150 | 50 | 78.5 | 1.06 | 211 | 361 | 130 | 100 | 80 | 3/8'-19 | 26 | 22 |
| RSC10 050 | 100 | 103.8 | 0.66 | 122 | 172 | 180 | 125 | 110 | 3/8'-19 | 28 | 24 |
| RSC10 0100 | 100 | 103.8 | 13.2 | 171 | 271 | 180 | 125 | 110 | 3/8'-19 | 28 | 30 |
| RSC10 0150 | 100 | 103.8 | 17.3 | 221 | 371 | 180 | 125 | 110 | 3/8'-19 | 28 | 45 |