HIGH PRESSURE PUMP

Single-Acting Short, Medium And Long Jacks

ISO9001 Supplier

Class Certificate

Export Supply

Single-Acting Short, Medium And Long Jacks   Model TCapacity cm²Area LOilcapacity mmHeight mmMaxHeight mmOutsidedia mmCylinderboredia mmPlungerdia mmoil inletthread mmb...



Key Highlights

Category	High Pressure Pump
Weight / Size	Single-Acting Short, Medium And Long Jacks Model TCapacity cm²Ar...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	High Pressure Pump	**Model / SKU**	Single-Acting-Short-Medium-And-Long-Jacks
Weight / Size	Single-Acting Short, Medium And Long Jacks Model TCapacity cm²Area LOilcapacity mmHeight mmMaxHeight mmOutsidedia mmCylinderboredia mmPlungerdia mmoil inletthread mmbulgeheight kgWeight RSC1050 10 13.8 0.073 107 157 64 46 40 3/8′-19 17 3 RSC10100 10 13.8 0.145 155 255 64 46 40 3/8′-19 17 3.5 RSC10150 10 13.8 0.22 206 361 64 46 40 3/8′-19 17 4.3 RSC2050 20 26.4 0.14 107 157 80 60 50 3/8′-19 20 5.5 RSC20100 20 26.4 0.28 155 255 80 60 50 3/8′-19 20 3 RSC20150 20 26.4 0.42 206 361 80 60 50 3/8′-19 20 10 RSC3050 30 41.8 0.208 112 162 100 80 70 3/8′-19 20 6.8 RSC30100 30 41.8 0.416 160 260 100 80 70 3/8′-19 20 12.5 RSC30150 30 41.8 0.624 211 361 100 80 70 3/8′-19 20 14.5 RSC5050 50 78.5 0.35 112 162 130 100 80 3/8′-19 26 9.8 RSC50100 50 78.5 0.7 160 260 130 100 80 3/8′-19 26 18 RSC50150 50 78.5 1.06 211 361 130 100 80 3/8′-19 26 22 RSC10050 100 103.8 0.66 122 172 180 125 110 3/8′-19 28 24 RSC100100 100 103.8 13.2 171 271 180 125 110 3/8′-19 28 30 RSC100150 100 103.8 17.3 221 371 180 125 110 3/8′-19 28 45	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

China Single-Acting Short, Medium And Long Jacks:

Single-Acting Short, Medium And Long Jacks

Model	T Capacity	cm² Area	L Oil capacity	mm Height	mm Max Height	mm Outside dia	mm Cylinder boredia	mm Plunger dia	mm oil inlet thread	mm bulge height	kg Weight

RSC10 50	10	13.8	0.073	107	157	64	46	40	3/8′-19	17	3
RSC10 100	10	13.8	0.145	155	255	64	46	40	3/8′-19	17	3.5
RSC10 150	10	13.8	0.22	206	361	64	46	40	3/8′-19	17	4.3
RSC20 50	20	26.4	0.14	107	157	80	60	50	3/8′-19	20	5.5
RSC20 100	20	26.4	0.28	155	255	80	60	50	3/8′-19	20	3
RSC20 150	20	26.4	0.42	206	361	80	60	50	3/8′-19	20	10
RSC30 50	30	41.8	0.208	112	162	100	80	70	3/8′-19	20	6.8
RSC30 100	30	41.8	0.416	160	260	100	80	70	3/8′-19	20	12.5
RSC30 150	30	41.8	0.624	211	361	100	80	70	3/8′-19	20	14.5
RSC50 50	50	78.5	0.35	112	162	130	100	80	3/8′-19	26	9.8
RSC50 100	50	78.5	0.7	160	260	130	100	80	3/8′-19	26	18
RSC50 150	50	78.5	1.06	211	361	130	100	80	3/8′-19	26	22
RSC10 050	100	103.8	0.66	122	172	180	125	110	3/8′-19	28	24
RSC10 0100	100	103.8	13.2	171	271	180	125	110	3/8′-19	28	30
RSC10 0150	100	103.8	17.3	221	371	180	125	110	3/8′-19	28	45