

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## MARINE NAVIGATION SIGNAL LIGHT

# Single-Deck Navigation Signal Light CXH-1D

ISO9001 Supplier

Class Certificate

Export Supply

The Navigation Signal Light used to the ship with length 50M or above as lamp signal liaison when night navigation.



### Key Highlights

<b>Category</b>	Marine Navigation Signal Light
<b>Standard</b>	ISO
<b>Material</b>	Steel
<b>Weight / Size</b>	Voltage 24V 110V 220V Power 60W 65W 65W Lamp Holder B22d Protection Clas...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	Marine Navigation Signal Light	<b>Model / SKU</b>	Single-Deck-Navigation-Signal-Light-CXH-1D
<b>Standard</b>	ISO	<b>Material</b>	Steel
<b>Weight / Size</b>	Voltage 24V 110V 220V Power 60W 65W 65W Lamp Holder B22d Protection Class IP55 Cable Diameter Dia.14-16 Name Type Visibility Level Arc Color Weight Starboard Light CXH1-1D 3n.m 112.5o Green 4.9KGS Port Light CXH2-1D 3n.m 112.5o Red 4.9KGS Masthead Light CXH3-1D 6n.m 225o White 4.9KGS Stern Light CXH4-1D 3n.m 135o White/Yellow 4.9KGS All-round-Light CXH6-1D 3n.m 360o Red/green/white 4.9KGS	<b>Surface</b>	The shell is made of steel, finished by special mold-powder with the feature of corrosion-resisting and shock resistance.
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

<b>CONTENTS</b>	<ul style="list-style-type: none"> <li>■ China Single-Deck Navigation Signal Light CXH-1D:</li> <li>■ Standards:</li> </ul>	<ul style="list-style-type: none"> <li>■ Products Advantage:</li> <li>■ Main Specification:</li> </ul>
-----------------	---	--

## China Single-Deck Navigation Signal Light CXH-1D:



The Navigation Signal Light used to the ship with length 50M or above as lamp signal liaison when night navigation.

### Products Advantage:

1. Easy to install and replace with bulb.



2. The shell is made of steel, finished by special mold-powder with the feature of corrosion-resisting and shock resistance.

3. PC Material, UV resistance and non-discolouring.

## Standards:

1. Confirm to the international regulation for preventing collision at sea, 1972 and grade entry norms for steel ships.

2. Confirm to the International Standard IEC60598-1-2008.

3. Confirm to the standard of marine electric signal light's technical condition GB/T 3028-2012.

## Main Specification:

Voltage	24V	110V	220V
Power	60W	65W	65W
Lamp Holder	B22d		
Protection Class	IP55		
Cable Diameter	Dia.14-16		

Name	Type	Visibility	Level Arc	Color	Weight
Starboard Light	CXH1-1D	3n.m	112.5°	Green	4.9KGS
Port Light	CXH2-1D	3n.m	112.5°	Red	4.9KGS
Masthead Light	CXH3-1D	6n.m	225°	White	4.9KGS
Stern Light	CXH4-1D	3n.m	135°	White/Yellow	4.9KGS
All-round- Light	CXH6-1D	3n.m	360°	Red/green/white	4.9KGS