

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## MARINE NAVIGATION SIGNAL LIGHT

# Single-Deck Navigation Signal Light CXH-2C

ISO9001 Supplier

Class Certificate

Export Supply

The Navigation Signal Light used to the ship with length 50M or above as lamp signal liaison when night navigation.



### Key Highlights

<b>Category</b>	Marine Navigation Signal Light
<b>Standard</b>	ISO
<b>Material</b>	Steel
<b>Weight / Size</b>	Voltage 24V 110V 220V Power 30W 65W 65W Lamp Holder B15d Protection Clas...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	Marine Navigation Signal Light	<b>Model / SKU</b>	Single-Deck-Navigation-Signal-Light-CXH-2C
<b>Standard</b>	ISO	<b>Material</b>	Steel
<b>Weight / Size</b>	Voltage 24V 110V 220V Power 30W 65W 65W Lamp Holder B15d Protection Class IP55 Cable Diameter Dia.10-12 Name Type Visibility Level Arc Color Weight Starboard Light CXH1-2C 3n.m 112.5o Green 1.8KGS Port Light CXH2-2C 3n.m 112.5o Red 1.8KGS Masthead Light CXH3-2C 5n.m 225o White 1.8KGS Stern Light CXH4-2C 3n.m 135o White/Yellow 1.8KGS All-round-Light CXH6-2C 3n.m 360o Red/green/white 1.8KGS	<b>Surface</b>	The shell is made of steel, finished by special mold-powder with the feature of corrosion-resisting and shock resistance.
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

<b>CONTENTS</b>	<ul style="list-style-type: none"> <li>■ China Single-Deck Navigation Signal Light CXH-2C:</li> <li>■ Standards:</li> </ul>	<ul style="list-style-type: none"> <li>■ Product Advantage:</li> <li>■ Main Specification:</li> </ul>
-----------------	---	---

## China Single-Deck Navigation Signal Light CXH-2C:



The Navigation Signal Light used to the ship with length 50M or above as lamp signal liaison when night navigation.

### Product Advantage:

1. Easy to install and replace with bulb.



2. The shell is made of steel, finished by special mold-powder with the feature of corrosion-resisting and shock resistance.

3. PC Material, UV resistance and non-discolouring.

## Standards:

1. Confirm to the international regulation for preventing collision at sea, 1972 and grade entry norms for steel ships.

2. Confirm to the International Standard IEC60598-1-2008.

3. Confirm to the standard of marine electric signal light's technical condition GB/T 3028-2012.

## Main Specification:

Voltage	24V	110V	220V
Power	30W	65W	65W
Lamp Holder	B15d		
Protection Class	IP55		
Cable Diameter	Dia.10-12		

Name	Type	Visibility	Level Arc	Color	Weight
Starboard Light	CXH1-2C	3n.m	112.5 <sup>0</sup>	Green	1.8KGS
Port Light	CXH2-2C	3n.m	112.5 <sup>0</sup>	Red	1.8KGS
Masthead Light	CXH3-2C	5n.m	225 <sup>0</sup>	White	1.8KGS
Stern Light	CXH4-2C	3n.m	135 <sup>0</sup>	White/Yellow	1.8KGS
All-round- Light	CXH6-2C	3n.m	360 <sup>0</sup>	Red/green/white	1.8KGS