

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## MARINE NAVIGATION SIGNAL LIGHT

# Single-Deck Navigation Signal Light CXH-3

ISO9001 Supplier

Class Certificate

Export Supply

The Navigation Signal Light used to the ship with length 12M or above as lamp signal liaison when night navigation.



### Key Highlights

<b>Category</b>	Marine Navigation Signal Light
<b>Standard</b>	ISO
<b>Material</b>	Steel
<b>Weight / Size</b>	Voltage 12V/24V Power 25W Lamp Holder B15d Protection Class IP55 Cable ...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	Marine Navigation Signal Light	<b>Model / SKU</b>	Single-Deck-Navigation-Signal-Light-CXH-3
<b>Standard</b>	ISO	<b>Material</b>	Steel
<b>Weight / Size</b>	Voltage 12V/24V Power 25W Lamp Holder B15d Protection Class IP55 Cable Diameter Dia.14 Name Type Visibility Level Arc Color Weight Starboard Light CXH1-3 1n.m 112.5o Green 1.05KGS Port Light CXH2-3 1n.m 112.5o Red 1.05KGS Masthead Light CXH3-3 2n.m 225o White 1.0KGS Stern Light CXH4-3 2n.m 135o White/Yellow 1.05KGS All- round- Light CXH6-3 2n.m 360o Red/green/white 0.85KGS	<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China

## China Single-Deck Navigation Signal Light CXH-3:



The Navigation Signal Light used to the ship with length 12M or above as lamp signal liaison when night navigation.

Standards:

1. Confirm to the international regulation for preventing collision at sea, 1972 and grade entry norms for steel ships.
2. Confirm to the International Standard IEC60598-1-2008.
3. Confirm to the standard of marine electric signal light's technical condition GB/T 3028-2012.

Main Specification:

Voltage	12V/24V
Power	25W



0.050924s

Lamp Holder	B15d
Protection Class	IP55
Cable Diameter	Dia.14

Name	Type	Visibility	Level Arc	Color	Weight
Starboard Light	CXH1-3	1n.m	112.5°	Green	1.05KGS
Port Light	CXH2-3	1n.m	112.5°	Red	1.05KGS
Masthead Light	CXH3-3	2n.m	225°	White	1.0KGS
Stern Light	CXH4-3	2n.m	135°	White/Yellow	1.05KGS
All-round- Light	CXH6-3	2n.m	360°	Red/green/white	0.85KGS