MARINE NAVIGATION SIGNAL LIGHT

Single-Deck Navigation Signal Light CXH-3

ISO9001 Supplier

Class Certificate

Export Supply

The Navigation Signal Light used to the ship with length 12M or above as lamp signal liaison when night navigation.



Key Highlights

Category	Marine Navigation Signal Light
Standard	ISO
Material	Steel
Weight / Size	Voltage 12V/24V Power 25W Lamp Holder B15d Protection Class IP55 Cable ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Navigation Signal Light	**Model / SKU**	Single-Deck-Navigation-Signal-Light-CXH-3
Standard	ISO	**Material**	Steel
Weight / Size	Voltage 12V/24V Power 25W Lamp Holder B15d Protection Class IP55 Cable Diameter Dia.14 Name Type Visibility Level Arc Color Weight Starboard Light CXH1-3 1n.m 112.5o Green 1.05KGS Port Light CXH2-3 1n.m 112.5o Red 1.05KGS Masthead Light CXH3-3 2n.m 225o White 1.0KGS Stern Light CXH4-3 2n.m 135o White/Yellow 1.05KGS All-round- Light CXH6-3 2n.m 360o Red/green/white 0.85KGS	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

China Single-Deck Navigation Signal Light CXH-3:



The Navigation Signal Light used to the ship with length12M or above as lamp signal liaison when night navigation.

Standards:

1. Confirm to the international regulation for preventing collision at sea, 1972 and grade entry norms for steel ships.

2. Confirm to the International Standard IEC60598-1-2008.

3. Confirm to the standard of marine electric signal light's technical condition GB/T 3028-2012.

Main Specification:

Voltage	12V/24V
Power	25W

Lamp Holder	B15d
Protection Class	IP55
Cable Diameter	Dia.14

Name	Type	Visibility	Level Arc	Color	Weight
Starboard Light	CXH1-3	1n.m	112.5^{o}	Green	1.05KGS
Port Light	CXH2-3	1n.m	112.5^{o}	Red	1.05KGS
Masthead Light	CXH3-3	2n.m	225^{o}	White	1.0KGS
Stern Light	CXH4-3	2n.m	135^{o}	White/Yellow	1.05KGS
All-round- Light	CXH6-3	2n.m	360^{o}	Red/green/white	0.85KGS