

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MARINE NAVIGATION SIGNAL LIGHT

Single-Deck Stainless Steel Navigation Signal Light CXH-1S

ISO9001 Supplier

Class Certificate

Export Supply

The Navigation Signal Light used to the ship with length 50M or above as lamp signal liaison when night navigation.



Key Highlights

Category	Marine Navigation Signal Light
Standard	ISO
Material	Stainless Steel
Weight / Size	Voltage 24V 110V 220V Power 30W 60W 65W Lamp Holder P28S Protection Clas...
Certificate	CCS Type Approval Certificate

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	Marine Navigation Signal Light	Model / SKU	Single-Deck-Stainless-Steel- Navigation-Signal-Light-CXH-1S
Standard	ISO	Material	Stainless Steel
Weight / Size	Voltage 24V 110V 220V Power 30W 60W 65W Lamp Holder P28S Protection Class IP56 Cable Diameter Dia.11 Name Type Visibility Level Arc Color Weight Starboard Light CXH1-1S 3n.m 112.5o Green 2.2KGS Port Light CXH2-1S 3n.m 112.5o Red 2.2KGS Masthead Light CXH3-1S 6n.m 225o White 2. KGS Stern Light CXH4-1S 3n.m 135o White/Yellow 2.3KGS All-round- Light CXH6-1S 3n.m 360o Red/green/white 2.0KGS	Certificate	CCS Type Approval Certificate
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	■ China Single-Deck Stainless Steel Navigation Signal Light CXH-1S:	■ Product Advantage:
	■ Standards:	■ Main Specification:

China Single-Deck Stainless Steel Navigation Signal Light CXH-1S:



The Navigation Signal Light used to the ship with length 50M or above as lamp signal liaison when night navigation.

Product Advantage:

1. Easy to Install and replace the bulb with a leakage hole at the bottom
2. The sheel is made of stainless steel, corrosion resistance and impact resistance



3. The shade is made of polycarbonate, UV Resistance and non-discolouring color.

Standards:

1. Confirm to the international regulation for preventing collision at sea, 1972 and grade entry norms for steel ships.
2. Confirm to the International Standard IEC60598-1-2008.
3. Confirm to the standard of marine electric signal light's technical condition GB/T 3028-2012.

Main Specification:

Voltage	24V	110V	220V
Power	30W	60W	65W
Lamp Holder	P28S		
Protection Class	IP56		
Cable Diameter	Dia.11		

Name	Type	Visibility	Level Arc	Color	Weight
Starboard Light	CXH1-1S	3n.m	112.5°	Green	2.2KGS
Port Light	CXH2-1S	3n.m	112.5°	Red	2.2KGS
Masthead Light	CXH3-1S	6n.m	225°	White	2. KGS
Stern Light	CXH4-1S	3n.m	135°	White/Yellow	2.3KGS
All-round- Light	CXH6-1S	3n.m	360°	Red/green/white	2.0KGS