

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MARINE WINDLASS

Single Hydraulic Combined Windlass

Single Hydraulic Combined Windlass General description The combined and capstan are for heaving, launching and mooring, which are in accordance with ISO4568-1986<>. They are driven by hand, electric,...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Windlass
Standard	ISO
Material	Cast steel
Certificate	CCS , Rina , ABS, BV, GL,

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Windlass	Model / SKU	Single-Hydraulic-Combined-Windlass
Standard	ISO	Material	Cast steel
Certificate	CCS , Rina , ABS, BV, GL,	Warranty	12 Months unless specified otherwise
Origin	China		

Single Hydraulic Combined Windlass

General description

The combined and capstan are for heaving, launching and mooring, which are in accordance with ISO4568-1986<>. They are driven by hand, electric, hydraulic and diesel engine. The structure types are divided into: systematic double-chain anchor winch (A type);single-chain anchor winch(B type) anchor capstan(E type).

Type illustration

The first letter: D-electric Y-hydraulic S-manual C-diesel engine

The letter M: anchor winch



The third letter: Type A,B,E

Main technical parameter

Type	anchor chain diam	workin g load		over loadin g		loadin g suppor t		nominal speed	Drum load	Nominal speed	Cable capacity	Moori ng line load
		A M 3	A M 2	A M 3	A M 2	A M 3	m / m in					
(mm)	AM2	A M 3	A M 2	A M 3	A M 2	A M 3	m / m in	Kn	m/min	m	Kn	
YMB-17.5	17.5	13	14.6	19.5	21.9	80	115	9	10	10	Φ11x100	8
YMB-19	19	15.3	17.2	23.8	25.8	95	135	9	15	10	Φ13x100	10
YMB-20	20	17.9	20	26.9	29	110	157	9	20	10	Φ13x100	10
YMB-22	22	20.6	23	30.9	34.5	126	180	9	20	15	Φ15x100	15
YMB-24	24	24.5	27.4	36.8	41.1	149	214	9	20	15	Φ15x100	20
YMB-26	26	28.7	32.1	43.1	48.2	175	250	9	20	10	Φ22x100	20
YMB-28	28	33.3	37.2	50.8	55.8	208	299	9	20	10	Φ22x120	20
YMB-30	30	38.3	42.8	57.5	64.2	241	330	9	30	10	Φ22x120	30
YMB-32	32	43.5	48.6	65.3	72.9	281	394	9	30	9	Φ20x120	30
YMB-34	34	49.1	54.9	73.3	82.4	334	461	9	40	9	Φ20x120	30
YMB-36	36	55.1	61.6	82.7	92.4	399	550	9	30	12	Φ20x120	30
YMB-38	38	61.4	68.9	92.1	103.4	465	652	9	40	15	Φ22x150	40

YMB-40	40	6 8	7 6	1 0 2	1 1 4	4 0 2	5 7 6	9	40	9	Φ22x150	40
YMB-42	42	7 5	8 3. 8	1 1 2. 5	1 2 5. 7	4 4 2	6 3 2	9	40	15	Φ22x150	50
YMB-44	44	8 2. 3	9 2	1 2 3. 5	1 3 8	4 8 3	6 9 1	9	50	15	Φ26x200	50
YMB-46	46	8 9. 9	1 0 0. 5	1 3 4. 9	1 5 0. 8	5 2 6	7 5 3	9	50	18	Φ26x200	50
YMB-48	48	9 7. 9	1 0 9. 4	1 4 6. 9	1 6 4. 1	5 7 0	8 1 6	9	60	10	Φ26x200	50
YMB-50	50	1 0 6. 3	1 1 8. 8	1 5 9. 5	1 7 8. 2	6 1 7	8 8 2	9	80	15	Φ26x200	50