MARINE OIL WATER SEPERATOR

Small-Sized Marine Oil Water Separator

The oil water separating device can be applied to small sized vehicle ship in freshwater,and meets the reqruiements of discharging standard of MEPC.107(49). The device consists of oil water separator,grasshopper,elect...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Oil Water Seperator
Standard	DIN
Material	Carbon Steel
Weight / Size	The oil water separating device can be applied to small sized vehicle sh...
Certificate	CCS, BV, ABS, GL，LR, NK

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Oil Water Seperator	**Model / SKU**	Small-Sized-Marine-Oil-Water-Separator
Standard	DIN	**Material**	Carbon Steel
Weight / Size	The oil water separating device can be applied to small sized vehicle ship in freshwater,and meets the reqruiements of discharging standard of MEPC.107(49).	**Certificate**	CCS, BV, ABS, GL，LR, NK
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- China Small-Sized Marine Oil Water Separator:
- Main technical parameter:

China Small-Sized Marine Oil Water Separator:

The oil water separating device can be applied to small sized vehicle ship in freshwater,and meets the reqruiements of discharging standard of MEPC.107(49). The device consists of oil water separator,grasshopper,electricity control box and something else. With compact structure,it is easy to operate,install and maintain.Besides that,it cau

ses no water pollution and saves oil and energy.

Oleaginous concetration of the contaminated water in the inlet:lowet than 150000PPM.

Working principle:It was designed according to the principle of gravity separation and coalescene,which composes the coarse separation and precise separation.

Main technical parameter:

Treatment capability	0.1 m3/hour	0.25 m3/hour
Discharging standard	Less than 15ppm	
Working pressure	Less than 0.2Mpa	
Matching water pump	CDZ-100	CDZ-250
Water pump, power supply of motor	AC380V or according to the demands of customers.	
Way of oil drainage	Manual / Automatic	
Size of sharp	640x370x670mm	690x405x800
Diameter of inlet and outlet pipe	1/2" pipe	
Weight	35kg	45kg

We still have other treatment capacity model,please contact us if you interested in it.