

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

NAVIGATION BUOY

Solid Anchor Mooring Buoy

Application area: Port, dock, mooring area Characteristic: anti-collision, anti-settling, good visual effect, with night fluorescent effect. Main Technical Parameters 1.

Diameter:1620mm ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Navigation Buoy
Standard	DIN
Material	Steel
Weight / Size	Total Weight:about 1500KG(on land)
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Navigation Buoy	Model / SKU	Solid-Anchor-Mooring-Buoy
Standard	DIN	Material	Steel
Weight / Size	Total Weight:about 1500KG(on land)	Surface	Surface Color:Orange, with night fluorescent effect(optional) 7.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Application area:

- Main Technical Parameters

Application area:

Port, dock, mooring area

Characteristic: anti-collision, anti-settling, good visual effect, with night fluorescent effect.



Main Technical Parameters

1. Diameter:1620mm
2. Length:2200mm
3. Material:CCS steel
4. Wall thickness:8mm
5. With polyurethane foam padding inside
6. Surface Color:Orange, with night fluorescent effect(optional)
7. Mooring Ring:50mm
8. Total Buoyancy:4T
9. Total Weight:about 1500KG(on land)