MARINE HOIST

Spring Balancer

ISO9001 Supplier

Class Certificate

Export Supply

Spring Balancer Spring balancers are suitable for assembly lines and various fixed positions where the workload is relatively concentrated.It is widely used for steam when operating tools are heavy and the d...



Key Highlights

Category	Marine Hoist
Standard	EN
Material	Model Balance the load (kg) The steel rope elongation(m) Weight (kg) EW-...
Weight / Size	Model Balance the load (kg) The steel rope elongation(m) Weight (kg) EW-...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Hoist	**Model / SKU**	Spring-Balancer
Standard	EN	**Material**	Model Balance the load (kg) The steel rope elongation(m) Weight (kg) EW-3 1-3 1.5/2.8 1.43 EW-5 3-5 1.5/2.8 1.52 EW-9 5-6 1.5/2.8 3.74 EW-15 9-15 1.5/2.8 3.9 EW-22 15-22 1.5/2.8 7.13 EW-30 22-30 1.5/2.8 7.6 EW-40 30-40 1.5/2.8 10 EW-50 40-50 1.5/2.8 10.2 EW-60 50-60 1.5/2.8 10.8 EW-70 60-70 1.5/2.8 11.2 EW-80 70-80 1.5/2.8 12 EWF-100 80-100 1.5/2.8 22 EWF-120 100-120 1.5/2.8 23 EWF-140 120-140 1.5/2.8 24 EWF-160 140-160 1.5/2.8 24.5 EWF-180 160-180 1.5/2.8 25 EWF-200 180-200 1.5/2.8 25.5
Weight / Size	Model Balance the load (kg) The steel rope elongation(m) Weight (kg) EW-3 1-3 1.5/2.8 1.43 EW-5 3-5 1.5/2.8 1.52 EW-9 5-6 1.5/2.8 3.74 EW-15 9-15 1.5/2.8 3.9 EW-22 15-22 1.5/2.8 7.13 EW-30 22-30 1.5/2.8 7.6 EW-40 30-40 1.5/2.8 10 EW-50 40-50 1.5/2.8 10.2 EW-60 50-60 1.5/2.8 10.8 EW-70 60-70 1.5/2.8 11.2 EW-80 70-80 1.5/2.8 12 EWF-100 80-100 1.5/2.8 22 EWF-120 100-120 1.5/2.8 23 EWF-140 120-140 1.5/2.8 24 EWF-160 140-160 1.5/2.8 24.5 EWF-180 160-180 1.5/2.8 25 EWF-200 180-200 1.5/2.8 25.5	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

China Spring Balancer:

Spring Balancer

Spring balancers are suitable for assembly lines and various fixed positions where the workload is relatively concentrated.It is widely used for steam when operating tools are heavy and the duration of using tools is long. Cars, tractors, household appliances and machinery manufacturing and other fields,whether in the assembly line Or working

at a fixed station,where manual tools and lifting equipment are used. Can be used, can also be used as an auxiliary tool for lifting tools. The tools are heavy and need to be When working frequently up and down, the lifting force of the balancer can be used to reduce labor.The purpose of strength.

Model	Balance the load (kg)	The steel rope elongation(m)	Weight (kg)
EW-3	1-3	1.5/2.8	1.43
EW-5	3-5	1.5/2.8	1.52
EW-9	5-6	1.5/2.8	3.74
EW-15	9-15	1.5/2.8	3.9
EW-22	15-22	1.5/2.8	7.13
EW-30	22-30	1.5/2.8	7.6
EW-40	30-40	1.5/2.8	10
EW-50	40-50	1.5/2.8	10.2
EW-60	50-60	1.5/2.8	10.8
EW-70	60-70	1.5/2.8	11.2
EW-80	70-80	1.5/2.8	12
EWF-100	80-100	1.5/2.8	22
EWF-120	100-120	1.5/2.8	23
EWF-140	120-140	1.5/2.8	24
EWF-160	140-160	1.5/2.8	24.5
EWF-180	160-180	1.5/2.8	25
EWF-200	180-200	1.5/2.8	25.5