

MANUAL OPERATED FIRE MONITOR

Stainless Steel Manual Fire Monitor PS80B

- ISO9001 Supplier
- Class Certificate
- Export Supply


Type: PS80B Flow Range: 0-80 L/S (0-1250GPM) Working Pressure: 10 bar Max Reach @ Max Flow: 80m Range of motion: -45°~+90°Vert , 360°Rot Max fog angle : 120° Horizontal Control : Lever Action Rotational Lock Materia...



Key Highlights

Category	Manual Operated Fire Monitor
Standard	EN
Material	-45°~+90°Vert , 360°Rot Max fog angle : 120° Horizontal Control : Lever Ac...
Weight / Size	-45°~+90°Vert , 360°Rot Max fog angle : 120° Horizontal Control : Lever Ac...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	Manual Operated Fire Monitor	Model / SKU	Stainless-Steel-Manual-Fire-Monitor-PS80B
Standard	EN	Material	-45°~+90°Vert , 360°Rot Max fog angle : 120° Horizontal Control : Lever Action Rotational Lock Material (body) : Stainless Steel Material (nozzle) : Aluminum Material (Tiller controll) : Stainless Steel Pump requirement for minimum performance : 30L/S@ 8 bar Pipe dimensions for installation:
Weight / Size	-45°~+90°Vert , 360°Rot Max fog angle : 120° Horizontal Control : Lever Action Rotational Lock Material (body) : Stainless Steel Material (nozzle) : Aluminum Material (Tiller controll) : Stainless Steel Pump requirement for minimum performance : 30L/S@ 8 bar Pipe dimensions for installation:	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China Stainless Steel Manual Fire Monitor PS80B:

Type: PS80B
 Flow Range: 0-80 L/S (0-1250GPM)
 Working Pressure: 10 bar
 Max Reach @ Max Flow: 80m
 Range of motion: -45°~+90°Vert , 360°Rot
 Max fog angle : 120°
 Horizontal Control : Lever Action Rotational Lock
 Material (body) : Stainless Steel
 Material (nozzle) : Aluminum
 Material (Tiller controll) : Stainless Steel
 Pump requirement for minimum performance : 30L/S@ 8 bar
 Pipe dimensions for installation: 4 Inch
 Monitor Inlet: DN100 flange
 Monitor Outlet : 2.5 inch (65mm)
 Paint: Fire Red

