

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

HIGH PRESSURE PUMP

Standard Tension Jack

Standard Tension Jack Model TCapacity mmmiddlehole mmOutsidedia mmCylinderboredia mmStroke pistonrod cm²;Area pressure ToolAnchor limitplate YCW-60 60 58 180 140 200 110 10362 57.9 90 100

ISO9001 Supplier

Class Certificate

Export Supply



jinbomarine.com

Key Highlights

Category	High Pressure Pump
Standard	EN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	High Pressure Pump	Model / SKU	Standard-Tension-Jack
Standard	EN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China Standard Tension Jack:

Standard Tension Jack

Model	T Capacity	mm middle hole	mm Outside dia	mm Cylinder boredia	mm Stroke	piston rod	cm ² Area	pressure	Tool Anchor	limit plate
YCW-60	60	58	180	140	200	110	10362	57.9	90	100
YCW-80	80	67	200	160	200	125	13737.5	58.23	100	123
YCW-100	100	78	230	180	200	140	17584	56.86	118	128

YCW-120	120	78	245	200	200	150	23550	50.95	118	128
YCW-150	150	100	270	220	200	170	24727.5	60.66	148	158
YCW-200	200	120	325	270	200	200	37130.5	53.86	168	178
YCW-250	250	130	350	290	200	220	43332	57.69	184	194
YCW-300	300	146	380	320	200	260	54950	54.59	214	214
YCW-350	350	165	400	340	200	260	59346	58.97	238	238
YCW-400	400	165	450	360	200	270	70336	56.86	248	248
YCW-450	450	175	480	380	200	280	78735.5	57.15	248	248
YCW-500	500	196	500	400	200	300	84.73.5	59.47	278	289
YCW-650	650	240	600	480	200	360	119320	54.47	318	338