

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## STEEL FIRE DOOR WITH WH

# Steel Fire proof door BT1NN2000GW with louver

1.60min/90min/180min fire rating 2. Panic bar, door closer, fireproof handle, stainless steel hinges 3. Mansony frame: 16 Gauge(cold roll steel or A60 Galv) 3 hours Warnock Hersey fire label

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

|             |                         |
|-------------|-------------------------|
| Category    | Steel fire door with WH |
| Material    | Cold roll steel& Galv   |
| Certificate | WH ITS                  |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

|          |                                      |             |   |
|----------|--------------------------------------|-------------|---|
| Category | Steel fire door with WH              | Model / SKU | Steel-Fire-proof-door-BT1NN2000GW-with-louver |
| Material | Cold roll steel& Galv                | Certificate | WH ITS  |
| Warranty | 12 Months unless specified otherwise | Origin      | China   |

## China Steel Fire proof door BT1NN2000GW with louver:

BT1NN2000GW with louver

1.60min/90min/180min fire rating

2. Panic bar, door closer, fireproof handle, stainless steel hinges

3. Mansony frame: 16 Gauge(cold roll steel or A60 Galv)

3 hours Warnock Hersey fire label



### Hollow Metal Door & Frame

(Fire Rating up to 3 hours & Positive Pressure)  
MECHANICALLY INTERLOCK SEAM, LAP SEAM, STITCHED SEAM AVAILABLE

Best Option For Commercial / Institutional / Industrial Entrances

Door Specs.

- Standard One Panel Doors:**
  - 18 Gauge
  - 24 Gauge
  - 30 Gauge
  - 36 Gauge
  - 42 Gauge
  - 48 Gauge
  - 54 Gauge
  - 60 Gauge
  - 66 Gauge
  - 72 Gauge
  - 78 Gauge
  - 84 Gauge
  - 90 Gauge
  - 96 Gauge
  - 102 Gauge
  - 108 Gauge
  - 114 Gauge
  - 120 Gauge
  - 126 Gauge
  - 132 Gauge
  - 138 Gauge
  - 144 Gauge
  - 150 Gauge
  - 156 Gauge
  - 162 Gauge
  - 168 Gauge
  - 174 Gauge
  - 180 Gauge
  - 186 Gauge
  - 192 Gauge
  - 198 Gauge
  - 204 Gauge
  - 210 Gauge
  - 216 Gauge
  - 222 Gauge
  - 228 Gauge
  - 234 Gauge
  - 240 Gauge
  - 246 Gauge
  - 252 Gauge
  - 258 Gauge
  - 264 Gauge
  - 270 Gauge
  - 276 Gauge
  - 282 Gauge
  - 288 Gauge
  - 294 Gauge
  - 300 Gauge
- Special Options:**
  - 18 Gauge
  - 24 Gauge
  - 30 Gauge
  - 36 Gauge
  - 42 Gauge
  - 48 Gauge
  - 54 Gauge
  - 60 Gauge
  - 66 Gauge
  - 72 Gauge
  - 78 Gauge
  - 84 Gauge
  - 90 Gauge
  - 96 Gauge
  - 102 Gauge
  - 108 Gauge
  - 114 Gauge
  - 120 Gauge
  - 126 Gauge
  - 132 Gauge
  - 138 Gauge
  - 144 Gauge
  - 150 Gauge
  - 156 Gauge
  - 162 Gauge
  - 168 Gauge
  - 174 Gauge
  - 180 Gauge
  - 186 Gauge
  - 192 Gauge
  - 198 Gauge
  - 204 Gauge
  - 210 Gauge
  - 216 Gauge
  - 222 Gauge
  - 228 Gauge
  - 234 Gauge
  - 240 Gauge
  - 246 Gauge
  - 252 Gauge
  - 258 Gauge
  - 264 Gauge
  - 270 Gauge
  - 276 Gauge
  - 282 Gauge
  - 288 Gauge
  - 294 Gauge
  - 300 Gauge

### Hollow Metal Door & Frame

(Fire Rating up to 3 hours & Positive Pressure)

Frame Specs.

- DRYWALL FRAMES:**
  - 18 Gauge
  - 24 Gauge
  - 30 Gauge
  - 36 Gauge
  - 42 Gauge
  - 48 Gauge
  - 54 Gauge
  - 60 Gauge
  - 66 Gauge
  - 72 Gauge
  - 78 Gauge
  - 84 Gauge
  - 90 Gauge
  - 96 Gauge
  - 102 Gauge
  - 108 Gauge
  - 114 Gauge
  - 120 Gauge
  - 126 Gauge
  - 132 Gauge
  - 138 Gauge
  - 144 Gauge
  - 150 Gauge
  - 156 Gauge
  - 162 Gauge
  - 168 Gauge
  - 174 Gauge
  - 180 Gauge
  - 186 Gauge
  - 192 Gauge
  - 198 Gauge
  - 204 Gauge
  - 210 Gauge
  - 216 Gauge
  - 222 Gauge
  - 228 Gauge
  - 234 Gauge
  - 240 Gauge
  - 246 Gauge
  - 252 Gauge
  - 258 Gauge
  - 264 Gauge
  - 270 Gauge
  - 276 Gauge
  - 282 Gauge
  - 288 Gauge
  - 294 Gauge
  - 300 Gauge
- MASONRY FRAMES:**
  - 18 Gauge
  - 24 Gauge
  - 30 Gauge
  - 36 Gauge
  - 42 Gauge
  - 48 Gauge
  - 54 Gauge
  - 60 Gauge
  - 66 Gauge
  - 72 Gauge
  - 78 Gauge
  - 84 Gauge
  - 90 Gauge
  - 96 Gauge
  - 102 Gauge
  - 108 Gauge
  - 114 Gauge
  - 120 Gauge
  - 126 Gauge
  - 132 Gauge
  - 138 Gauge
  - 144 Gauge
  - 150 Gauge
  - 156 Gauge
  - 162 Gauge
  - 168 Gauge
  - 174 Gauge
  - 180 Gauge
  - 186 Gauge
  - 192 Gauge
  - 198 Gauge
  - 204 Gauge
  - 210 Gauge
  - 216 Gauge
  - 222 Gauge
  - 228 Gauge
  - 234 Gauge
  - 240 Gauge
  - 246 Gauge
  - 252 Gauge
  - 258 Gauge
  - 264 Gauge
  - 270 Gauge
  - 276 Gauge
  - 282 Gauge
  - 288 Gauge
  - 294 Gauge
  - 300 Gauge
- DOUBLE-EGRESS:**
  - 18 Gauge
  - 24 Gauge
  - 30 Gauge
  - 36 Gauge
  - 42 Gauge
  - 48 Gauge
  - 54 Gauge
  - 60 Gauge
  - 66 Gauge
  - 72 Gauge
  - 78 Gauge
  - 84 Gauge
  - 90 Gauge
  - 96 Gauge
  - 102 Gauge
  - 108 Gauge
  - 114 Gauge
  - 120 Gauge
  - 126 Gauge
  - 132 Gauge
  - 138 Gauge
  - 144 Gauge
  - 150 Gauge
  - 156 Gauge
  - 162 Gauge
  - 168 Gauge
  - 174 Gauge
  - 180 Gauge
  - 186 Gauge
  - 192 Gauge
  - 198 Gauge
  - 204 Gauge
  - 210 Gauge
  - 216 Gauge
  - 222 Gauge
  - 228 Gauge
  - 234 Gauge
  - 240 Gauge
  - 246 Gauge
  - 252 Gauge
  - 258 Gauge
  - 264 Gauge
  - 270 Gauge
  - 276 Gauge
  - 282 Gauge
  - 288 Gauge
  - 294 Gauge
  - 300 Gauge

33

34

**LISTING REPORT - MANUFACTURING**  
Issued: Jul 17 2006 5:38PM

Inspection Tests And Evaluation Of

**Mexin Series 1200, 1600, 1800 3-Hour Polystyrene Core Steel Fire Door (13901)**

RENDERED TO  
**Chongqing Mexin Messon Doors Industry Co., Ltd.**  
No. 51 Baihe Road  
Chongqing,  
CHINA

**GENERAL:** This Report gives the results of the inspection, tests and evaluation of the above for compliance with applicable requirements of the following standards: ASTM E152-81a UL 10(c) (1998) UBC 7-2 (1997) UBC 7-2 (1994) UL 10(b) (1997) ASTM E2074 (2000) NFPA 252 (2003) CAN / ULC S104 1980 R1985

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. To verify a listing, call 888-347-3473, or check our searchable online Directory of Listed Products at www.intertek.com.