NAVIGATION BUOY

Steel Navigation Buoy

Steel Navigation Buoy used as Navigation Marks in Ocean, Inland River and Offshore Oil Platform, diameter is from 0.5M to 8M. Main Specification Type Dia....

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Navigation Buoy
Material	Steel
Weight / Size	Main Specification Type Dia. (m) Lamp Bracket(m) Focal Plane Height(m) La...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Navigation Buoy	**Model / SKU**	Steel-Navigation-Buoy
Material	Steel	**Weight / Size**	Main Specification Type Dia.(m) Lamp Bracket(m) Focal Plane Height(m) Lamp Draught(m) Buoy Depth(m) Weight(T) JB0.8-D1 0.8 1.0-1.5 1.5-2.0 LED 0.5-1.5 3.5-15 0.6 JB1.0-D1 1 1.5-2.0 2.0-2.5 LED 1.5-1.5 3.5-15 0.8 JB1.2-D1 1.2 2.0-3.0 2.5-3.5 LED 1.5-2.8 3.5-15 0.9 JB1.5-D1 1.5 2.0-3.0 2.5-3.5 LED 1.5-2.8 3.5-15 1.2 JB1.8-D1 1.8 3.0-4.0 3.6-4.8 LED 1.5-2.8 6-25 1.8 JB2.4-D1 2.4 3.0-4.0 3.5-5.5 LED 2.0-3.0 13-40 4.2 JB3.0-D1 3 3.5-5.0 4.5-6.0 LED 2.0-3.0 13-40 4.8 JB3.6-D1 3.6 3.5-5.0 4.5-6.0 LED 2.0-3.0 13-40 5.8 JB6.0-D1 6 4.5-6.0 4.5-6.0 LED 2.0-3.0 13-40 * JB8.0-D1 8 6.0-12 6.0-12 LED 2.0-3.0 20-80 *
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		


CONTENTS

- China Steel Navigation Buoy:
- Main Specification

China Steel Navigation Buoy:

Steel Navigation Buoy used as Navigation Marks in Ocean, Inland River and Offshore Oil Platform, diameter is from 0.5M to 8M.

Main Specification



Type	Dia.(m)	Lamp Bracket(m)	Focal Plane Height(m)	Lamp	Draught(m)	Buoy Depth(m)	Weight(T)

JB0.8-D1	0.8	1.0-1.5	1.5-2.0	LED	0.5-1.5	3.5-15	0.6
JB1.0-D1	1	1.5-2.0	2.0-2.5	LED	1.5-1.5	3.5-15	0.8
JB1.2-D1	1.2	2.0-3.0	2.5-3.5	LED	1.5-2.8	3.5-15	0.9
JB1.5-D1	1.5	2.0-3.0	2.5-3.5	LED	1.5-2.8	3.5-15	1.2
JB1.8-D1	1.8	3.0-4.0	3.6-4.8	LED	1.5-2.8	6-25	1.8
JB2.4-D1	2.4	3.0-4.0	3.5-5.5	LED	2.0-3.0	13-40	4.2
JB3.0-D1	3	3.5-5.0	4.5-6.0	LED	2.0-3.0	13-40	4.8
JB3.6-D1	3.6	3.5-5.0	4.5-6.0	LED	2.0-3.0	13-40	5.8
JB6.0-D1	6	4.5-6.0	4.5-6.0	LED	2.0-3.0	13-40	*
JB8.0-D1	8	6.0-12	6.0-12	LED	2.0-3.0	20-80	*