IEC 60092 STANDARD CABLE (KOREA TYPE)

TFOI Flame Retardant Marine Telephone Cable 250V (Light Weight Cable)

ISO9001 Supplier

Class Certificate

Export Supply

TFOI Marine Telephone Cable (150V/250V) is Flame Retardant and Light Weight Cable. Cable Construction   Conductor: Tinned Copper. IEC 60228 Class 2 Insulation : XLP...



Key Highlights

Category	IEC 60092 Standard Cable (Korea Type)
Standard	EN
Material	Tinned Copper/XLPE insulation/SHF1 sheath/Tinned Copper Wire Braided/SHF...
Weight / Size	TFOI Marine Telephone Cable (150V/250V) is Flame Retardant and Light Wei...
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.


Technical Specifications

Category	IEC 60092 Standard Cable (Korea Type)	**Model / SKU**	TFOI-Flame-Retardant-Marine-Telephone-Cable-250V-Light-Weight-Cable
Standard	EN	**Material**	Tinned Copper/XLPE insulation/SHF1 sheath/Tinned Copper Wire Braided/SHF1
Weight / Size	TFOI Marine Telephone Cable (150V/250V) is Flame Retardant and Light Weight Cable.	**Certificate**	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- China TFOI Flame Retardant Marine Telephone Cable 250V (Light Weight Cable):
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application

China TFOI Flame Retardant Marine Telephone Cable 250V (Light Weight Cable):



TFOI Marine Telephone Cable (150V/250V) is Flame Retardant and Light Weight Cable.

Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Insulation : XLPE Insulation

Inner Covering: Halogen-Free Tape

Armour : Copper Wire Braided

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

Standards

Design : IEC 60092-350, 376

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1P, 2P,3P,4P,5P,7P,10P,12P,14P,16P,19P,20P, 24P, 30P (P:Pair)

1T, 2T,3T,4T,5T,7T,10T,12T,14T,16T,19T,20T, 24T, 30T (Triad)

Size (sqmm): 0.75, 1, 1.5, 2.5

Feature

Halogen-free, Low Smoke, Flame retadant

Application

The cable is fixed installation on ships and offshore units, used for telephone and instrument.