IEC 60092 STANDARD CABLE (KOREA TYPE)


TICI/TIOI Flame Retardant Marine Telephone & Instrument Cable 250V (Non-screen)

ISO9001 Supplier

Class Certificate

Export Supply

TICI and TIOI Cable(150/250V) is non screen Flame Retardant Marine Telephone & Instrument cable, we supply these cable to Singapore, Indonesia, Malaysia, Thailand and other countries. Technical Speci...



Key Highlights

Category	IEC 60092 Standard Cable (Korea Type)
Standard	EN
Material	Tinned Copper/XLPE insulation/SHF1 sheath/Galvanized Steel Wire Braided/...
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	IEC 60092 Standard Cable (Korea Type)	**Model / SKU**	TICI-TIOI-Flame-Retardant-Marine-Telephone-Instrument-Cable-250V-Non-screen
Standard	EN	**Material**	Tinned Copper/XLPE insulation/SHF1 sheath/Galvanized Steel Wire Braided/SHF1
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	**Surface**	Galvanized
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China TICI/TIOI Flame Retardant Marine Telephone & Instrument Cable 250V (Non-screen):
- Cable Construction
- Cores & Size
- Technical Specification：
- Standards
- Feature

China TICI/TIOI Flame Retardant Marine Telephone & Instrument Cable 250V (Non-screen):



TICI and TIOI Cable(150/250V) is non screen Flame Retardant Marine Telephone & Instrument cable, we supply these cable to Singapore, Indonesia, Malaysia, Thailand and other countries.

Technical Specification：

Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Insulation : XLPE Insulation

Inner Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

Armour : Galvanized Wire Braided/Tinned Copper Wire Braied

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1), Black

Standards

Design : IEC 60092-350, 376

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A

Fire-resistant: IEC 60331

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1P, 2P,3P,4P,5P,7P,10P,12P,14P,16P,19P,20P, 24P, 30P (P:Pair)

1T, 2T,3T,4T,5T,7T,10T,12T,14T,16T,19T,20T, 24T, 30T (Triad)

Size (sqmm): 0.75, 1, 1.5, 2.5

Feature

Halogen-free, Low Smoke, Flame retardant.