

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MOORING LINE


TONSBERG Mooring Link


Tonsberg mooring link is galvanized steel mooring link of compact design typically used as connection between wire rope and fibre tail. there is three size available, 90Ton, 120Ton and 180Ton.

ISO9001 Supplier

Class Certificate

Export Supply

C = 136 mm	C = 150 mm	C = 160 mm	 <p>Each link is proof tested and certified by DNV. DNV type approval certificate No. S-4718</p>
D = 65 mm	D = 75 mm	D = 85 mm	
E = 75 mm	E = 90 mm	E = 120 mm	
R = 22 mm	R = 28 mm	R = 30 mm	
Breaking load: 90 Tonnes	Breaking load: 120 Tonnes	Breaking load: 180 Tonnes	
Proof Load: 55 Tonnes	Proof Load: 70 Tonnes	Proof Load: 95 Tonnes	
Weight: 11,2 Kg	Weight: 16,9 Kg	Weight: 25 Kg	



Fibre rope around the bolt, wire rope around the body.

Tonsberg Mooring Link with roller		Tonsberg Mooring Link 300 T	
	120T	180T	A = 447 mm
Opening E =	90mm	120mm	B = 216 mm
Roller dia D =	82mm	97mm	C = 190 mm
			D = 110 mm
			E = 146 mm
			R = 36 mm

Category	Mooring Line
Standard	EN
Material	Steel
Weight / Size	there is three size available, 90Ton, 120Ton and 180Ton.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Mooring Line	Model / SKU	TONSBERG-Mooring-Link
Standard	EN	Material	Steel
Weight / Size	there is three size available, 90Ton, 120Ton and 180Ton.	Surface	galvanized
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ China TONSBERG Mooring Link:	■ IMPA Code:
----------	--------------------------------	--------------

China TONSBERG Mooring Link:

Tonsberg mooring link is galvanized steel mooring link of compact design typically used as connection between wire rope and fibre tail. there is three size available, 90Ton, 120Ton and 180Ton.

Proof Load: 55Ton, 70Ton, 95Ton



Breaking Load: 90ton, 120Ton, 180ton

Weight: 11.2kg, 16.9kgs, 25kgs



IMPA Code:

IMPA Code	Product Description
211151	Link Mooring Tonsberg 90Ton
211152	Link Mooring Tonsberg 120Ton
211153	Link Mooring Tonsberg 180Ton

Tonsberg Mooring Link - galvanized steel mooring link of compact design typically utilized as connection between wire rope and fibre tail. Available in three sizes 90 T, 120 T and 180 T. 300 T can be supplied on special request.

Link 90 T	Link 120 T	Link 180 T
Tail 56-68 mm	Tail 72-80 mm	Tail 88-112 mm
A = 285 mm	A = 324 mm	A = 350 mm
B = 115 mm	B = 142 mm	B = 184 mm
C = 136 mm	C = 150 mm	C = 160 mm
D = 65 mm	D = 75 mm	D = 85 mm
E = 75 mm	E = 90 mm	E = 120 mm
R = 22 mm	R = 20 mm	R = 30 mm
Breaking load: 90 Tonnes	Breaking load: 120 Tonnes	Breaking load: 180 Tonnes
Proof Load: 55 Tonnes	Proof Load: 70 Tonnes	Proof Load: 95 Tonnes
Weight: 11.2 Kg	Weight: 16.9 Kg	Weight: 25 Kg

Each link is proof tested and certified by DNV. DNV type approval certificate No. 2-4729

Fibre rope around the bolt, wire rope around the body.

Tonsberg Mooring Link with roller		Tonsberg Mooring Link 300 T
120T	180T	A = 447 mm
Opening E = 90mm	120mm	B = 216 mm
Roller dia D = 82mm	97mm	C = 190 mm
		D = 110 mm
		E = 146 mm
		R = 36 mm
		Breaking load: 300 Tonnes
		Soft working Load: 150 Tonnes
		Weight: 52 Kg
		With works certificate