

SHORE POWER CABLE


TPNP Three Cores Shore Power Cable 0.6/1KV

ISO9001 Supplier

Class Certificate

Export Supply

JIS C 3410-1999 Shore Power Cable 0.6/1KV TPNP Cable is Three Cores Portable or Flexible cable, used for Shore Power Cable and Portable Cable. 0.6/1KV DPNP Cable is Double Cores Portable or Flexible ca...

| | |
|--|---|
|  | Key Highlights |
| | Category Shore Power Cable |
| | Standard JIS |
| | Material Tinned Copper/EP Rubber/PCP Sheath |
| | Weight / Size IEC 60332-1 & IEC 60332-3 Category A Cores & Size Number of Conductor: |
| Certificate ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | |
| We can supply according to your requirement, drawings, class certificate needs, and delivery schedule. | |

Technical Specifications

| | | | |
|----------------------|--|--------------------|--|
| Category | Shore Power Cable | Model / SKU | TPNP-Three-Cores-Shore-Power-Cable-0-6-1KV |
| Standard | JIS | Material | Tinned Copper/EP Rubber/PCP Sheath |
| Weight / Size | IEC 60332-1 & IEC 60332-3 Category A Cores & Size Number of Conductor: | Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |
| Warranty | 12 Months unless specified otherwise | Origin | China |

CONTENTS

- China TPNP Three Cores Shore Power Cable 0.6/1KV:
- Standards
- Feature
- Cable Construction
- Cores & Size



0.037371s

China TPNP Three Cores Shore Power Cable 0.6/1KV:



JIS C 3410-1999 Shore Power Cable

0.6/1KV TPNP Cable is Three Cores Portable or Flexible cable, used for Shore Power Cable and Portable Cable.

0.6/1KV DPNP Cable is Double Cores Portable or Flexible cable, used for Shore Power Cable and Portable Cable.

0.6/1KV FPNP Cable is Four cors Portable or Flexible cable, used for Shore Power Cable and Portable Cable.

Cable Construction

| Classification | Code | Construction details |
|----------------|----------------------------|------------------------------|
| Conductor | T | Tinned Copper Wire JIS C3410 |
| Insulation | P | EP Rubber as per JIS C 3410 |
| Covering | N | PCP as per JIS C 3410 |
| Color: Black | | |
| p | Portable or Flexible Cable | |

Standards

Design : JIC C 3410(1999)

Flammability: IEC 60332-1 & IEC 60332-3 Category A

Cores & Size

Number of Conductor: 3Core

Size of Conductor (mm²):1, 1.5 2.5 4 6 10 16 25 35 50, 75, 95

Feature

Halogen-free, Low Smoke, Flame retardant

