

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

BOW THRUSTER

Tanker Bow Thrusters

A bow thruster provide a side directional thrust force to ensure the best performance under all kinds of weather and water conditions, the bow thruster able to provide a sufficient for the boat in which it has been ins...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Bow Thruster
Standard	EN
Certificate	CCS,ABS,LR,BV,DNV etc.

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Bow Thruster	Model / SKU	Tanker-Bow-Thrusters
Standard	EN	Certificate	CCS,ABS,LR,BV,DNV etc.
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Tanker Bow Thrusters:
- Advantages:
- Specifications:

China Tanker Bow Thrusters:



A bow thruster provide a side directional thrust force to ensure the best performance under all kinds of weather and water conditions, the bow thruster able to provide a sufficient for the boat in which it has been installed.

We specialize at design, manufacture and supply bow thruster. Technology is from Schottel Sweden, ensure reliable quality with competitive price.

Advantages:

1. For extreme load conditions, e.g. in the offshore sector
2. Low noise emission
3. Available with either fixed or controllable-pitch propellers
4. Can be diesel, hydraulic or electric drive

Specifications:

Controllable pitch propeller tunnel thruster parameters							
Model	CP-1000	CP-1100	CP-1300	CP-1650	CP-2000	CP-2400	CP-2800
Max input power	280	315/335	445/480	680/730	1050/900	1580/1720	2000/1910
Ratio	3.09	3.09	3.78	4.72	4.82	4.645	4.395
Max input speed	1450/1750	1450/1750	1450/1750	1450/1750	1450/1190	980/1190	980/880
Propeller speed	469.1/560	469/566	384/463	307/370	301/247	211/256	223/200
Propeller diameter	1000	1100	1300	1650	2000	2400	2800
Max thrust	43	46/47	66/67	97/105	155/144	239/242	298/297
Cylinder length	1045	1045	1190	1446	1680	1990	2280
Cylinder internal	1020	1120	1328	1680	2030	2430	2836