HIGH PRESSURE PUMP

# Thin Self-Locking Jack

ISO9001 Supplier

Class Certificate

Export Supply

Thin Self-Locking Jack   Product features: Low profile design for tight spaces where standard cylinders cannot be used. Nut self-locking for long-term safe and secure load support. Single-acting design, gravity...




## Key Highlights

| | |
|---|---|
| **Category** | High Pressure Pump |
| **Standard** | EN |
| **Weight / Size** | Model TCapacity mmStroke mm Height mmMax Height mmDiameter kgW... |
| **Certificate** | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

| | | | |
|---|---|---|---|
| **Category** | High Pressure Pump | **Model / SKU** | Thin-Self-Locking-Jack |
| **Standard** | EN | **Weight / Size** | Model TCapacity mmStroke mm Height mmMax Height mmDiameter kgWeight CLP-602 60 50 125 175 140 15 CLP-1002 100 50 137 187 175 26 CLP-1602 160 45 148 193 220 44 CLP-2002 200 45 155 200 245 57 CLP-2502 250 45 159 204 275 74 CLP-4002 400 45 178 223 350 134 CLP-5002 500 45 192 237 400 189 |
| **Certificate** | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | **Warranty** | 12 Months unless specified otherwise |
| **Origin** | China | | |

## China Thin Self-Locking Jack:

Thin Self-Locking Jack

Product features:

Low profile design for tight spaces where standard cylinders cannot be used.

Nut self-locking for long-term safe and secure load support.

Single-acting design, gravity reset.

Special composite coating for increased corrosion resistance and reduced friction for flexible movement.

Overflow hole and limited stroke function.

| Model | T<br>Capacity | mm<br>Stroke | mm<br>Height | mm<br>Max Height | mm<br>Diameter | kg<br>Weight |
|---|---|---|---|---|---|---|
| CLP-602 | 60 | 50 | 125 | 175 | 140 | 15 |
| CLP-1002 | 100 | 50 | 137 | 187 | 175 | 26 |
| CLP-1602 | 160 | 45 | 148 | 193 | 220 | 44 |
| CLP-2002 | 200 | 45 | 155 | 200 | 245 | 57 |
| CLP-2502 | 250 | 45 | 159 | 204 | 275 | 74 |
| CLP-4002 | 400 | 45 | 178 | 223 | 350 | 134 |
| CLP-5002 | 500 | 45 | 192 | 237 | 400 | 189 |