

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

HIGH PRESSURE PUMP

Thin Self-Locking Jack

Thin Self-Locking Jack Product features: Low profile design for tight spaces where standard cylinders cannot be used. Nut self-locking for long-term safe and secure load support. Single-acting design, gravity...

- ISO9001 Supplier
- Class Certificate
- Export Supply



jinbomarine.com

Key Highlights

Category	High Pressure Pump
Standard	EN
Weight / Size	Model TCapacity mmStroke mm Height mmMax Height mmDiameter kgW...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	High Pressure Pump	Model / SKU	Thin-Self-Locking-Jack
Standard	EN	Weight / Size	Model TCapacity mmStroke mm Height mmMax Height mmDiameter kgWeight CLP-602 60 50 125 175 140 15 CLP-1002 100 50 137 187 175 26 CLP-1602 160 45 148 193 220 44 CLP-2002 200 45 155 200 245 57 CLP-2502 250 45 159 204 275 74 CLP-4002 400 45 178 223 350 134 CLP- 5002 500 45 192 237 400 189
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China Thin Self-Locking Jack:

Thin Self-Locking Jack

Product features:

Low profile design for tight spaces where standard cylinders cannot be used.

Nut self-locking for long-term safe and secure load support.

Single-acting design, gravity reset.

Special composite coating for increased corrosion resistance and reduced friction for flexible movement.

Overflow hole and limited stroke function.

Model	T Capacity	mm Stroke	mm Height	mm Max Height	mm Diameter	kg Weight
CLP-602	60	50	125	175	140	15
CLP-1002	100	50	137	187	175	26
CLP-1602	160	45	148	193	220	44
CLP-2002	200	45	155	200	245	57
CLP-2502	250	45	159	204	275	74
CLP-4002	400	45	178	223	350	134
CLP-5002	500	45	192	237	400	189