LIFE JACKET

Three Pieces Work Vest

ISO9001 Supplier

Class Certificate

Export Supply

Product Description:
Its floating core adopts imported foam material, the surface is something like PVC plastic. The products are widely&nb...



Key Highlights

Category	Life Jacket
Standard	ISO
Material	Its floating core adopts imported foam material, th e surface is somethin...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Life Jacket	**Model / SKU**	Three-Pieces-Work-Vest
Standard	ISO	**Material**	Its floating core adopts imported foam material, the sur face is something like PVC plastic. The products are widely used in the weari ng of the maritime crew, oil platform workers.Ships and inland river ships, in line with the 96 amendment is ap plicable for sea on the crew, oil platform workers to we ar, and for ship, marine facilities, port, wharf operation.
Surface	Its floating core adopts imported foam material, the sur face is something like PVC plastic. The products are widely used in the weari ng of the maritime crew, oil platform workers.Ships and inland river ships, in line with the 96 amendment is ap plicable for sea on the crew, oil platform workers to we ar, and for ship, marine facilities, port, wharf operation.	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- Product Description:
- Parameter:

Product Description:

Its floating core adopts imported foam material, the surface is something like PVC plastic. The products are widely used in the wearing of the maritime crew, oil platform workers.Ships and inland river ships, in line with the 96 amendment is applicable for sea on the crew, oil platform workers to wear, and for ship, marine facilities, port, wharf operation.

Parameter:

1. Floating core: bubble Surface: PVC plastic

2. Pass ISO12402 Testing

3. Buoyancy: >150N

4. Floating time: ≥24h

5. Ambient temperature: -30℃~ 65℃

6. Period of validity: 3 years