MARINE WINDLASS

Two-chain Lifter Hydraulic Windlass

ISO9001 Supplier

Class Certificate

Export Supply

Two-chain Lifter Hydraulic Windlass General description The combined and capstan are for heaving, launching and mooring,which are in accordance with ISO4568-1986<>. They are dr...



Key Highlights

Category	Marine Windlass
Standard	ISO
Material	Cast steel
Certificate	CCS，Rina，ABS, BV, GL,

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Windlass	Model / SKU	Two-chain-Lifter-Hydraulic-Windlass
Standard	ISO	Material	Cast steel
Certificate	CCS，Rina，ABS, BV, GL,	Warranty	12 Months unless specified otherwise
Origin	China		

China Two-chain Lifter Hydraulic Windlass:



Two-chain

Lifter Hydraulic Windlass

General description

The combined and capstan are for heaving, launching and mooring,which are in accordance with ISO4568-1986<>. They are driven by hand,electric,hydraulic and diesel engine. The structure types are divided into:systematic double-chain anchor winch(A type);single-chain anchor winch(B type) anchor capstan(E type).

Type illustration

the first letter: D-electric Y-hydraulic S-manual C-diesel engine

the letter M:anchor winch

the third letter: Type A,B,E

Main technical parameter

Type	anchor chain diam	working load		over loading		loading support		nominal speed	mooring line load
(mm)	AM2	AM3	AM2	AM3	AM2	AM3	m/min	Kn	
YMA-17.5	17.5	13	14.6	19.5	21.9	80	115	9	8
YMA-19	19	15.3	17.2	23	25.8	95	135	9	10
YMA-20	20	17.9	20	26.9	30	110	157	9	10
YMA-22	22	20.6	23	30.9	34.5	126	180	9	15
YMA-24	24	24.5	27.4	36.8	41.1	149	214	9	20
YMA-26	26	28.7	32.1	43.1	48.2	175	250	9	20
YMA-28	28	33.3	37.2	50	55.8	202	289	9	20
YMA-30	30	38.3	42.8	57.5	64.2	231	330	9	30

YMA-32	32	43.5	48.6	65.3	72.9	261	374	9	30
YMA-34	34	49.1	54.9	73.3	82.4	294	421	9	30
YMA-36	36	55.1	61.6	82.7	92.4	329	470	9	30
YMA-38	38	61.4	68.9	92.1	103.4	365	522	9	40
YMA-40	40	68	76	102	114	402	576	9	40
YMA-42	42	75	83.8	112.5	125.7	442	632	9	50
YMA-44	44	82.3	92	123.5	138	483	691	9	50
YMA-46	46	89.9	100.5	134.9	150.8	526	753	9	50
YMA-48	48	97.9	109.4	146.9	164.1	570	816	9	50
YMA-50	50	106.3	118.8	159.5	178.2	617	882	9	50