

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

WALL PANEL

Type C Wall Panel

Type C Wall Panel Model Thickness Fire class Core material B100C 100MM A-6...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

| | |
|----------------------|---|
| Category | Wall Panel |
| Standard | EN |
| Material | Galvanized/ Stainless steel plate with PVC film and rock wool |
| Weight / Size | Type C Wall Panel Model Thickness Fire class Core material B100C 100MM A... |
| Certificate | ABS, LR, BV, GL, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

| Technical Specifications | | | |
|--------------------------|--|--------------------|---|
| Category | Wall Panel | Model / SKU | Type-C-Wall-Panel |
| Standard | EN | Material | Galvanized/ Stainless steel plate with PVC film and rock wool |
| Weight / Size | Type C Wall Panel Model Thickness Fire class Core material B100C 100MM A-60 rock wool B50C 50mm B-15 rock wool B30C 30mm B-15 rock wool B25C 25mm B-0 rock wool B25C 25mm B-0 Aluminum honeycomb SB25C ≥75mm B-30/B-15 rock wool B50CD 50mm B-15 rock wool B50CGa 50mm B-15 rock wool Main Specification Type B100C B50C B30C Fire class A-60 B-15 B-15 Weight 24.8kg/m ² 16.1kg/m ² 13.7kg/m ² Sound reduction 32dB 33dB --dB Thermal transmittance 0.33Kcal/m ² h°C 0.58Kcal/m ² h°C 0.93Kcal/m ² h°C Core material Rock wool 150kg/m ³ Surface finish PVC film(150μ,low flame spread) or galvanized steel Dimension 30/50/100mm(t)×550mm(w)×length (max.3500mm) Tolerances Thickness0-1×Width0-1×Length±3 | Surface | galvanized |
| Certificate | ABS, LR, BV, GL, CCS | Warranty | 12 Months unless specified otherwise |
| Origin | China | | |

| | | |
|-----------------|---------------------|----------------------|
| CONTENTS | ■ Type C Wall Panel | ■ Main Specification |
|-----------------|---------------------|----------------------|



Type C Wall Panel

| Model | Thickness | Fire class | Core material |
|--------|-----------|------------|--------------------|
| B100C | 100MM | A-60 | rock wool |
| B50C | 50mm | B-15 | rock wool |
| B30C | 30mm | B-15 | rock wool |
| B25C | 25mm | B-0 | rock wool |
| B25C | 25mm | B-0 | Aluminum honeycomb |
| SB25C | ≥75mm | B-30/B-15 | rock wool |
| B50CD | 50mm | B-15 | rock wool |
| B50CGa | 50mm | B-15 | rock wool |

Main Specification

| Type | B100C | B50C | B30C |
|-----------------------|--|-----------------------------|-----------------------------|
| Fire class | A-60 | B-15 | B-15 |
| Weight | 24.8kg/m ² | 16.1kg/m ² | 13.7kg/m ² |
| Sound reduction | 32dB | 33dB | --dB |
| Thermal transmittance | 0.33Kcal/m ² h°C | 0.58Kcal/m ² h°C | 0.93Kcal/m ² h°C |
| Core material | Rock wool 150kg/m ³ | | |
| Surface finish | PVC film(150μ, low flame spread) or galvanized steel | | |
| Dimension | 30/50/100mm(t)×550mm(w)×length (max.3500mm) | | |
| Tolerances | Thickness0-1×Width0-1×Length±3 | | |