

NAVIGATION BUOY

# Visual & Radio Aids to Navigation

Specifications Type HD160-Y1 HD155-Y1 Voltage DC12V DC12V Power ...

- ISO9001 Supplier
- Class Certificate
- Export Supply

HD155-Y1

HD160-Y1

### Key Highlights

<b>Category</b>	Navigation Buoy
<b>Standard</b>	EN
<b>Weight / Size</b>	Specifications Type HD160-Y1 HD155-Y1 Voltage DC12V DC12V Power 8W 10W S...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	Navigation Buoy	<b>Model / SKU</b>	Visual-Radio-Aids-to-Navigation
<b>Standard</b>	EN	<b>Weight / Size</b>	Specifications Type HD160-Y1 HD155-Y1 Voltage DC12V DC12V Power 8W 10W Source LED Navigation LED Navigation Range >4.5nm >6.4nm Characteristic 256 program 256 program Color Red, Yellow, Green, White Red, Yellow, Green, White Optical sensitivity 300LX 300LX Working Environment Outdoor Waterproof Outdoor Waterproof Protection IP65 IP65 Working Temperature -25-65°C -25-65°C Installation 4-Φ13/Φ195mm 4-Φ13/Φ195mm Weight 11kgs 11kgs
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		



## Specifications

Type	HD160-Y1	HD155-Y1
Voltage	DC12V	DC12V
Power	8W	10W
Source	LED Navigation	LED Navigation
Range	>4.5nm	>6.4nm
Characteristic	256 program	256 program
Color	Red, Yellow, Green, White	Red, Yellow, Green, White
Optical sensitivity	300LX	300LX
Working Environment	Outdoor Waterproof	Outdoor Waterproof
Protection	IP65	IP65
Working Temperature	-25-65°C	-25-65°C
Installation	4-Φ13/Φ195mm	4-Φ13/Φ195mm
Weight	11kgs	11kgs