SENSOR

# WFS-2 Wind speed sensor

ISO9001 Supplier

Class Certificate

Export Supply

Power supply: DC 12-36V Measurement range:0.1 ~40 m/s Accuracy : < 30m/s±(0.5+0.05v) ≥ 30m/s±5% Starting speed: < 0.1m/s Response time : < 0.5s Working Temperature - 20°C~ + 70°C Humidity : 20% - 90% RH(25...




## Key Highlights

| | |
|---|---|
| **Category** | Sensor |
| **Standard** | EN |
| **Material** | 20% - 90% RH(25℃ No condensation) Material:ABS + PC Output signal type: |
| **Certificate** | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

| | | | |
|---|---|---|---|
| **Category** | Sensor | **Model / SKU** | WFS-2-Wind-speed-sensor |
| **Standard** | EN | **Material** | 20% - 90% RH(25℃ No condensation) Material:ABS + PC Output signal type: |
| **Certificate** | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | **Warranty** | 12 Months unless specified otherwise |
| **Origin** | China | | |

## China WFS-2 Wind speed sensor:

Power supply: DC 12-36V
Measurement range:0.1 ~40 m/s
Accuracy : < 30m/s±(0.5+0.05v) ≥ 30m/s±5%
Starting speed: < 0.1m/s
Response time : < 0.5s
Working Temperature - 20°C~ + 70°C
Humidity : 20% - 90% RH(25℃ No condensation)
Material:ABS + PC

Output signal type:
WFS-2-2 : 4~20 mA
WFS-2-3 : 0 ~ 5 V
WFS-2-4 : RS 485

