

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

SEWAGE PUMP

WQ (K) cutting submersible Sewage pump

ISO9001 Supplier

Class Certificate

Export Supply

WQ (K) cutting submersible pump Application Severely polluted waste water of factories, residence, hospitals, hotels, municipal works, marsh gas tanks in countryside, dredging of river and sea. Featur...



Key Highlights

Category	Sewage Pump
Standard	EN
Material	Cast iron, stainless steel
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Sewage Pump	Model / SKU	WQ-K-cutting-submersible-Sewage-pump
Standard	EN	Material	Cast iron, stainless steel
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- WQ (K) cutting submersible pump
- Features
- Specification
- Application
- Model Implication



WQ (K) cutting submersible pump

Application

Severely polluted waste water of factories, residence, hospitals, hotels, municipal works, marsh gas tanks in countryside, dredging of river and sea.

Features

With casing of stainless steel precision casting, it is corrosion-resistant, environment-friendly, durable, high in head and large in flow rate. It uses motor of F insulation grade. On the base of this style, the pump can be installed with automatic agitator device, which rotates with shaft of motor, produces very strong agitation force, inhale sediments in the sump after mixes blend to become session to the pump then eject it. Pump more than 11kw could be with double-protection function.

Model Implication

50(JY)WQ D10-10-0.75S

50: Outlet diameter 50mm

JY: Automatic agitator

WQ: Sewage Submersible pump

D: single phase submersible pump (three phase without "D")

10: Rated capacity 10m³/h

10: Rated head 10m

0.75: Power 0.75kw

S: Stainless steel

Specification

Model	Capacity (m ³ /h)	Head (m)	Power (KW)	Voltage (V)	Outlet Diameter(mm)
100WQ80-15-7.5S	80	15	7.5	380	100
100WQ80-10-5.5S	80	10	5.5	380	100
100WQ50-7-2.2S	50	7	2.2	380	100
100WQ50-15-4S	50	15	4	380	100
100WQ50-10-3S	50	10	3	380	100
100WQ100-35-22S	100	35	22	380	100
100WQ100-30-18.5S	100	30	18.5	380	100



100WQ100-25-15S	100	25	15	380	100
100WQ100-20-11S	100	20	11	380	100