SENSOR

WS-BJD Alarm Light

ISO9001 Supplier

Class Certificate

Export Supply

Explosive-Proof Grade:Ex dII BT6.   Working Voltage:DC24V Alarm Current: < 100mA (DC24V)   Flicker Frequency: 60 times/min   Alarm Volu...



Key Highlights

Category	Sensor
Standard	EN
Weight / Size	95% RH (Prohibit dew) Atmospheric Pressure:80kPa~110kPa Weight:1...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Sensor	**Model / SKU**	WS-BJD-Alarm-Light
Standard	EN	**Weight / Size**	95% RH (Prohibit dew) Atmospheric Pressure:80kPa~110kPa Weight:1.2kg
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

China WS-BJD Alarm Light:

Explosive-Proof Grade:Ex dII BT6.

Working Voltage:DC24V

Alarm Current: < 100mA (DC24V)

Flicker Frequency: 60 times/min

Alarm Volume:90~100dB

Environmental Temperature: -30~70 degree centigrade

Humidity: 95% RH (Prohibit dew)

Atmospheric Pressure:80kPa~110kPa

Weight:1.2kg