SENSOR

WS-ZS-500T Semi-Submersible Platform Windlass Load Sensor

ISO9001 Supplier

Class Certificate

Export Supply

Range:50~500 Ton. Accuracy:0.02   Sensitivity:1.6 ± 0.005mv/V input Resistance:380 ±20Ω Output Resistance:350   ±2Ω Insulation Resistance: >5000...





Key Highlights

Category	Sensor
Standard	EN
Material	0~20mV Voltage analog signals. Material:Stainless steel.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Sensor	**Model / SKU**	WS-ZS-500T-Semi-Submersible-Platform-Windlass-Load-Sensor
Standard	EN	**Material**	0~20mV Voltage analog signals. Material:Stainless steel.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

China WS-ZS-500T Semi-Submersible Platform Windlass Load Sensor:

Range:50~500 Ton.

Accuracy:0.02

Sensitivity:1.6 ± 0.005mv/V

input Resistance:380 ±20Ω

Output Resistance:350 ±2Ω

Insulation Resistance: >5000 mΩ

The biggest bridge voltage:15V

Safe Overload:120% F.S.

Temperature Range: -30~70 degree centigrade.

Output Signal: 0~20mV Voltage analog signals.

Material:Stainless steel.