

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

SENSOR

WS-ZS Weight Sensor

Range: 50kg to 500ton. Application: Load sensing, transfer transportation system, wire rope pull strength measurement. Accuracy of measurement: $1.0 \pm 0.005 \text{mv/v}$; ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Sensor
Standard	EN
Material	$1.0 \pm 0.005 \text{mv/v}$ Ultimate overload:250%F.S Protection Class:IP68 Saf...
Weight / Size	50kg to 500ton. Application:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Sensor	Model / SKU	WS-ZS-Weight-Sensor
Standard	EN	Material	$1.0 \pm 0.005 \text{mv/v}$ Ultimate overload:250%F.S Protection Class:IP68 Safe Overload:150%F.S Temperature range:-30 to 70 centigrade Features: Built-in film sensing element. Stainless steel material. The integrated amplifier circuit. Long term stability. Strong impact resistance. Suitable for dynamic and static measurements.
Weight / Size	50kg to 500ton. Application:	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

■ China WS-ZS Weight Sensor:

■ Features:

China WS-ZS Weight Sensor:

Range: 50kg to 500ton.

Applicaton:

Load sensing,transfer transportation system,wire rope pull strength measurement.

Accuracy of measurement: 1.0 ± 0.005 mv/v

Ultimate overload:250%F.S

Protection Class:IP68

Safe Overload:150%F.S

Temperature range:-30 to 70 centigrade

Features:

Built-in film sensing element.

Stainless steel material.

The integrated amplifier circuit.

Long term stability.

Strong impact resistance.

Suitable for dynamic and static measurements.

Tiny temperature drift error.