


SENSOR

WTF-B500 Anemometer

Power supply: 24V, 220V,380V(±20%) Measurement range:0.1 ~40 m/s Accuracy : < 30m/s±(0.5+0.05v) ≥ 30m/s±5% Starting speed: < 0.2m/s Response time : < 1s Working Temperature - 20°C~ + 70°C Humidity : 20% - ...

- ISO9001 Supplier
- Class Certificate
- Export Supply



Key Highlights

Category	Sensor
Standard	EN
Material	20% - 90% RH(25°C No condensation) Anemometer type:digital Material:ABS e...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Sensor	Model / SKU	WTF-B500-Anemometer
Standard	EN	Material	20% - 90% RH(25°C No condensation) Anemometer type:digital Material:ABS engineering plastic
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China WTF-B500 Anemometer:

Power supply: 24V, 220V,380V(±20%)
 Measurement range:0.1 ~40 m/s
 Accuracy : < 30m/s±(0.5+0.05v) ≥ 30m/s±5%
 Starting speed: < 0.2m/s
 Response time : < 1s
 Working Temperature - 20°C~ + 70°C

Humidity : 20% - 90% RH(25°C No condensation)

Anemometer type:digital

Material:ABS engineering plastic

