MARINE TEMPERATURE INSTRUMENT

WTQ Gas Type Pressure Type Thermometer

ISO9001 Supplier

Class Certificate

Export Supply

Product Description: It is an electrical switch that can make electric circuit close or open according to the change of controlled medium temperature. It can be used In ship,freeze equipment or other industrial equ...



Key Highlights

Category	Marine Temperature Instrument
Standard	DIN
Material	Model Measurement range(℃) Accuracy Adjsutment range of insert length of...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Temperature Instrument	**Model / SKU**	WTQ-Gas-Type-Pressure-Type-Thermometer
Standard	DIN	**Material**	Model Measurement range(℃) Accuracy Adjsutment range of insert length of temperature bulb （mm) Temperature bulb diameter Connection thread Casing material WTZ-280 -40~60 -60~80 0~50 0~100 0~150 20~120 60~160 1.5 150-2000 15mm M27x2 G1/2" G3/4“ Phenolic resin Copper alloy Stainless steel WTQ-280 -60~40 -40~60 0~200 0~250 0~300 0~400 0~500 2.5 320-420 22mm Type Capillary tube length(m) Temperature bulb and capillary tube material Maximum length of capillary tube Normal type 1~20 T2 20 Anti-corrosive type 1~10 1Cr18Ni9Ti 15
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Product Description:
- Main Technical Specification:

Product Description:

It is an electrical switch that can make electric circuit close or open according to the change of controlled medium temperature. It can be used In ship,freeze equipment or other industrial equipment,carry two position controlling to the temperature of gas,liquid or steam.

Dial diameter : 100mm and 150mm available.

WTZ type is Steam type.

WTQ type is Gas type.

Main Technical Specification:

Model	Measurement range(℃)	Accuracy	Adjsutment range of insert length of temperature bulb （mm)	Temperature bulb diameter	Connection thread	Casing material

WTZ-280	-40~60 -60~80 0~500 0~100	0~150 20~120 60~160	1.5	150-2000	15mm	M27x2 G1/2" G3/4“	Phenolic resin Copper alloy Stainless steel
WTQ-280	-60~40 -40~60	0~200 0~250 0~300 0~400 0~500	2.5	320-420	22mm		

Type	Capillary tube length(m)	Temperature bulb and capillary tube material	Maximum length of capillary tube
Normal type	1~20	T2	20
Anti-corrosive type	1~10	1Cr18Ni9Ti	15

