

SENSOR

WZPK-21R-C-E Type Temperature Transmitter

ISO9001 Supplier

Class Certificate

Export Supply

Product Description: WZPK-21R-C-E Type Temperature Transmitter adopt high quality platinum resistor as temperature sensing element,it features high measuring accuracy,steady and reliability,long lifetime. It has wide...



Key Highlights

Category	Sensor
Standard	EN
Material	Model Temperature-sensing element Measuring range Protective cover Nomin...
Certificate	CCS,GL,LR,BV,ABS,DNV GL,RINA,NK,KR ETC.

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Sensor	Model / SKU	WZPK-21R-C-E-Type-Temperature-Transmitter
Standard	EN	Material	Model Temperature-sensing element Measuring range Protective cover Nominal pressure Output signal Material Diameter WZPK pt100 pt500 pt1000 -70~500 centigrade SUS304 SUS316L single/double layer 12mm 16mm 1.0Mpa Output resistance(2 wires,3 wires) Output DC 4~20mA(2 wires) Model Design:
Certificate	CCS,GL,LR,BV,ABS,DNV GL,RINA,NK,KR ETC.	Warranty	12 Months unless specified otherwise
Origin	China		



CONTENTS	■ Product Description:	■ Main Technical Specification:
	■ Model Design:	

Product Description:

WZPK-21R-C-E Type Temperature Transmitter adopt high quality platinum resistor as temperature sensing element, it features high measuring accuracy, steady and reliability, long lifetime. It has widely used to measure temperature of liquid, gas and steam in ship and other industrial equipment.

Main Technical Specification:

Model	Temperature-sensing element	Measuring range	Protective cover		Nominal pressure	Output signal
			Material	Diameter		
WZPK	pt100 pt500 pt1000	-70~500 centigrade	SUS304 SUS316L single/double layer	12mm 16mm	1.0Mpa	Output resistance(2 wires, 3 wires) Output DC 4~20mA(2 wires)

Model Design:

● 型号标记 MODEL SIGN

W Z P K - □ □ - C - □ □

- S-附加现场显示型 Appending local indication
- E-本安型 B-隔爆型 D-附加Pt100输出
- E-Intrinsic safety B-Explosion proof housing D-Pt100 Outp
- 船用型 Marine
- 输出信号 Output signal
- 1-输出4~20mA 1-Output4~20mA
- R-Pt电阻值 R-Pt resistance
- 保护管型式 Thermowell type
- 1- 1/2"单保护管 single thermowell
- 2- φ16双保护管 double thermowell
- 3- 其他型式 Other types
- 安装固定型式 Mounting type
- 1-可动内螺纹接头 Movable female screw connector
- 2-可动外螺纹接头 Movable male screw connector
- 3-活动法兰式 Loose flange type
- 4-固定法兰式 Fixed flange type
- 铠装式 Armor type
- 铂电阻传感器 Pt resistance sensor
- 热电阻 Heat resistance
- 温度仪表 Temperature instrument

WZPK-221-C-E WZPK-221-C-B

WZPK-21R(j)-C-D WZPK-23R-C WZPK-221-C-S