

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## CHAIN STOPPER

## Wire Rope Carpenter Stopper

Carpenter Stoppers have a hinged body that has a fixed smooth groove on one side. It is movable wedge, grooved with lay of cable, on the facing side. The movable wedge enables the cable to be drawn tight. They are ind...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

Category	Chain Stopper
Standard	EN
Material	Steel
Weight / Size	Rugged, compact design cable grip for cable sizes from 5/16" to 3".
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

Category	Chain Stopper	Model / SKU	Wire-Rope-Carpenter-Stopper
Standard	EN	Material	Steel
Weight / Size	Rugged, compact design cable grip for cable sizes from 5/16" to 3".	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

#### CONTENTS

- China Wire Rope Carpenter Stopper: Specification:
- Carpenter Stopper Drawing

### China Wire Rope Carpenter Stopper:

Carpenter Stoppers have a hinged body that has a fixed smooth groove on one side. It is movable wedge, grooved with lay of cable, on the facing side. The movable wedge enables the cable to be drawn tight. They are individually proof tested to twice the working load limit of XIP wire rope.



The cable can be released while under the full tension by releasing the latch on the hinged lid. The Lid is securely latched and locked with a pin while in use.

Shackle holes are provided for rigging a bridle to the stopper. Bridles are available with stoppers if desired.

Rugged, compact design cable grip for cable sizes from 5/16" to 3".

### Specification:

Proof Load: 1.5xSWL

Breaking Load: 5xSWL

wire rope d	kN (tf)	Size													Weight kg
		L	L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	L <sub>4</sub>	L <sub>5</sub>	S	S <sub>1</sub>	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	R		
1 φ15.0~ 19.5 (5.1)	50	180	56	150	91	33	82	10	14	20	16	12	20	12	
2 φ19.5~ 26.0 (10.2)	100	235	68	200	105	38	89	12	16	24	18	14	24	16	
3 φ26.0~ 32.5 (14.8)	145	270	75	230	120	42.5	110	16	22	27	20	16	27	20	
4 φ32.5~ 39.0 (25)	245	300	94	255	148	51.5	135	20	26	32	24	18	32	25	
5 φ39.0~ 52.0 (39.8)	390	330	108	280	176	62	154	28	36	36	28	20	36	30	
6 φ52.0~ 65.0 (69.9)	685	390	130	340	224	77	185	40	48	44	34	22	44	30	

### Carpenter Stopper Drawing

