LIFE JACKET

# XT5582A Automatic 150N Inflatable Lifejacket

ISO9001 Supplier

Class Certificate

Export Supply

It features high in strength,steady in performance,light in weight, and small in size.Meanwhile the key parts of the lifejacket are imported from abroad. For example, high-strength material coating with polyurethane,b...




## Key Highlights

| | |
|---|---|
| **Category** | Life Jacket |
| **Standard** | EN |
| **Material** | Polyurethane |
| **Weight / Size** | It features high in strength,steady in performance,light in weight, and ... |
| **Certificate** | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

| | | | |
|---|---|---|---|
| **Category** | Life Jacket | **Model / SKU** | XT5582A-Automatic-150N-Inflatable-Lifejacket |
| **Standard** | EN | **Material** | Polyurethane |
| **Weight / Size** | It features high in strength,steady in performance,light in weight, and small in size.Meanwhile the key parts of the lifejacket are imported from abroad. | **Certificate** | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |
| **Warranty** | 12 Months unless specified otherwise | **Origin** | China |

**CONTENTS**

- China XT5582A Automatic 150N Inflatable Lifejacket:
- Main technical Parmaeter:

## China XT5582A Automatic 150N Inflatable Lifejacket:

It features high in strength,steady in performance,light in weight, and small in size.Meanwhile the key parts of the lifejacket are imported from abroad. For example, high-strength material coating with polyurethane,bobbin etc.It is one of the most advanced on-water life-saving products both at home and overseas. Application:it has a wide use in many fields,such as the army,ocean and inland navigation,fishery,anti-trafficking boats,cruiser and yacht etc.

## Main technical Parmaeter:

| Model number | XT5582A ( Automatic ) | XT5582M ( Hand operated type ) |
|---|---|---|
| Air chamber quantity | 1 | 1 |
| Air chamber material | Polyurethane | Polyurethane |
| Inlet and out let air nozzle ( quantity ) | 1 | 1 |
| Air inflation type | Automatic | Hand operated type |
| Inflation time | <5s | <3s |
| CO2gas weight ( g ) | 33 | 33 |
| Buoyancy ( N ) | >150N | >150N |