

## LIFE JACKET

# XT5582A Automatic 150N Inflatable Lifejacket

ISO9001 Supplier

Class Certificate

Export Supply

It features high in strength, steady in performance, light in weight, and small in size. Meanwhile the key parts of the lifejacket are imported from abroad. For example, high-strength material coating with polyurethane, b...



## Key Highlights

Category	Life Jacket
Standard	EN
Material	Polyurethane
Weight / Size	It features high in strength, steady in performance, light in weight, and ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

Category	Life Jacket	Model / SKU	XT5582A-Automatic-150N-Inflatable-Lifejacket
Standard	EN	Material	Polyurethane
Weight / Size	It features high in strength, steady in performance, light in weight, and small in size. Meanwhile the key parts of the lifejacket are imported from abroad.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

### CONTENTS

- China XT5582A Automatic 150N Inflatable Lifejacket:

- Main technical Parameter:



## China XT5582A Automatic 150N Inflatable Lifejacket:

It features high in strength, steady in performance, light in weight, and small in size. Meanwhile the key parts of the lifejacket are imported from abroad. For example, high-strength material coating with polyurethane, bobbin etc. It is one of the most advanced on-water life-saving products both at home and overseas. Application: it has a wide use in many fields, such as the army, ocean and inland navigation, fishery, anti-trafficking boats, cruiser and yacht etc.

### Main technical Parameter:

Model number	XT5582A ( Automatic )	XT5582M ( Hand operated type )
Air chamber quantity	1	1
Air chamber material	Polyurethane	Polyurethane
Inlet and out let air nozzle ( quantity )	1	1
Air inflation type	Automatic	Hand operated type
Inflation time	<5s	<3s
CO <sub>2</sub> gas weight ( g )	33	33
Buoyancy ( N )	>150N	>150N