


MARINE PRESSURE INSTRUMENT

YC-M Type Diaphragm Sealed Pressure Gauge

- ISO9001 Supplier
- Class Certificate
- Export Supply

Product Description: Diaphragm sealed pressure gauge can be used to measure pressure of liquid which have the characteristic of corrosive,high viscosity,easily riming,solid state granule,higher temperature in ship ...

	<p>Key Highlights</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;">Category</td> <td style="padding: 5px;">Marine Pressure Instrument</td> </tr> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;">Standard</td> <td style="padding: 5px;">EN</td> </tr> <tr> <td style="background-color: #1a3d4d; color: white; padding: 5px;">Certificate</td> <td style="padding: 5px;">CCS, GL, LR, BV, ABS, DNV, RINA, NK, KR and EC certificate.</td> </tr> </table> <p style="font-size: small; padding-top: 10px;">We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.</p>	Category	Marine Pressure Instrument	Standard	EN	Certificate	CCS, GL, LR, BV, ABS, DNV, RINA, NK, KR and EC certificate.
Category	Marine Pressure Instrument						
Standard	EN						
Certificate	CCS, GL, LR, BV, ABS, DNV, RINA, NK, KR and EC certificate.						

Technical Specifications			
Category	Marine Pressure Instrument	Model / SKU	YC-M-Type-Diaphragm-Sealed-Pressure-Gauge
Standard	EN	Certificate	CCS, GL, LR, BV, ABS, DNV, RINA, NK, KR and EC certificate.
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	<ul style="list-style-type: none"> ■ Product Description: 	<ul style="list-style-type: none"> ■ Main technical specification:
-----------------	--	---

Product Description:

Diaphragm sealed pressure gauge can be used to measure pressure of liquid which have the characteristic of corrosive,high viscosity,easily riming,solid state granule,higher temperature in ship and industrial equipment.

Main technical specification:

Measure range:-0.1-0MPa,0-0.1~60MPa



Accuracy: 1.6,2.5

Medium temperature: Equal or less than 80 centigrade

型号标记 MODEL SIGN

YC-100 M- - - -

- Q- 遥测 Remote measuring
- X- 信号远传 (Ex ia II CT6) Output signal
- N- 表头充液耐震型 Dial is liquid filled and anti-vibration type YC-100M-B-M-N-QX
- 接口型式 Connection type
- M M1- 螺纹型 Screw thread type
- F F1 F2 F3- 法兰型 Flange type
- 壳体材料 Material of body :
- B- 不锈钢 Stainless steel
- 隔膜式 Diaphragm sealed type
- 表面直径 Dial dia.
- 船用压力表 Marine pressure gauge

隔膜装置尺寸 THE MOUNTING DIMENSION

型式 Model	测量上限 Upper limit	法兰标准 Flange standard	D	K	d	f	L	C	B	图号 Drawing No.	材料 Material
F	4MPa	GB2506-2005	185	145	122	3	18	20	65	图一 Figure I	SUS304 SUS316
F1	6-10MPa		165	125	102	3	18	20	50	图二 Figure II	
	16-25MPa		115	85	68	2	14	18	25		

W